



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## MHUB3 1" Mall Cond HB *Crouse-Hinds*

Catalog Number	MHUB3
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Mhub Conduit Hub, Malleable Iron, 1"
Weight per unit	0.4200 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

### Features

connection	Male Threaded
dimensions	2.0600 IN X 1.8100 IN X 1.7900 IN
Material	Malleable Iron

### Material, Color, and Finish

Finish	Zinc Electroplated
--------	--------------------

### Dimensions and Weight

Size	1 in
------	------

### Descriptions

Description	1" MALL COND HB
extra long description	MIDWEST MHUB3 1 COND HUB MALLEABLE
Features	The use of rigid/IMC conduit remains the preferred choice in many applications because of the physical protection of conductors and long service life of the installation. Consequently, the need to terminate conduit into a box or enclosure creates the need for a hub. The Crouse-Hinds series commercial hub has been developed to provide a lightweight hub that installs quickly and easily, providing a secure termination.
Long Description	Eaton Crouse-Hinds series MHUB conduit hub, Malleable iron, 1"
Product Type	1 Cond Hub Malleable Iron
Special Features	Weight 50 Lb per 100

### Manufacturer Information

Brand	Eaton
GTIN	00784564002877
Manufacturers Part Number	MHUB3
UPC	784564002877

### Taxonomies, Classifications, and Categories

Category Description	STEEL EMT FITTINGS
Type	Conduit hub

### Packaging

Carton	5
Weight Per each	0.42



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
Enclosure standard	NEMA FB-1, Class I Div 2, Class II Div 1 2, Class III Div 1 2 UL 514B, CUL, CSA C22.2