



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



MHUB5 1-1/2" CNDT Hub

Crouse-Hinds

Catalog Number	MHUB5
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Mhub Conduit Hub, Malleable Iron, 1-1/2"
Weight per unit	0.2000 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

connection	Male Threaded
dimensions	3.1300 IN X 2.7600 IN X 2.0500 IN
Material	Malleable Iron

Material, Color, and Finish

Finish	Zinc Electroplated
--------	--------------------

Dimensions and Weight

Size	1-1/2 in
------	----------

Descriptions

Description	1-1/2" CNDT HUB
extra long description	MIDWEST MHUB5 1 1/2 COND HUB MALLEA
Features	The use of rigid/IMC conduit remains the preferred choice in many applications because of the physical protection of conductors and long service life of the installation. Consequently, the need to terminate conduit into a box or enclosure creates the need for a hub. The Crouse-Hinds series commercial hub has been developed to provide a lightweight hub that installs quickly and easily, providing a secure termination.
Long Description	Eaton Crouse-Hinds series MHUB conduit hub, Malleable iron, 1-1/2"
Product Type	1 1/2 Cond Hub Malleable Iron
Special Features	Weight 20 Lb per 100

Manufacturer Information

Brand	Eaton
GTIN	00784564002891
Manufacturers Part Number	MHUB5
UPC	784564002891

Taxonomies, Classifications, and Categories

Category Description	Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS AND THREADLESS CONNECTOR
Type	Conduit hub



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	2
Weight Per each	0.2

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
Enclosure standard	NEMA FB-1, Class I Div 2, Class II Div 1 2, Class III Div 1 2 UL 514B, CUL, CSA C22.2