



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

9707 Broadway St Suite 100
78217-0000, TX San Antonio
Phone: 210-646-6950
Fax: 210-646-6192



MHUB8 3" CNDT Hub *Crouse-Hinds*

Catalog Number	MHUB8
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Mhub Conduit Hub, Malleable Iron, 3"
Weight per unit	0.0500 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

connection	Male Threaded
dimensions	5.0500 IN X 4.4400 IN X 3.1500 IN
Material	Malleable Iron

Material, Color, and Finish

Finish	Zinc Electroplated
--------	--------------------

Dimensions and Weight

Size	3 in
------	------

Descriptions

Description	3" CNDT HUB
extra long description	MIDWEST MHUB8 3 COND HUB MALLEABLE
Features	The use of rigid/IMC conduit remains the preferred choice in many applications because of the physical protection of conductors and long service life of the installation. Consequently, the need to terminate conduit into a box or enclosure creates the need for a hub. The Crouse-Hinds series commercial hub has been developed to provide a lightweight hub that installs quickly and easily, providing a secure termination.
Long Description	Eaton Crouse-Hinds series MHUB conduit hub, Malleable iron, 3"
Product Type	3 Cond Hub Malleable Iron
Special Features	Weight 5 Lb per 100

Manufacturer Information

Brand	Eaton
GTIN	00784564002921
Manufacturers Part Number	MHUB8
UPC	784564002921

Taxonomies, Classifications, and Categories

Category Description	Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS AND THREADLESS CONNECTOR
Type	Conduit hub



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

9707 Broadway St Suite 100
78217-0000, TX San Antonio
Phone: 210-646-6950
Fax: 210-646-6192

Packaging

Carton	1
Weight Per each	0.05

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - Other
Enclosure standard	NEMA FB-1, Class I Div 2, Class II Div 1 2, Class III Div 1 2 UL 514B, CUL, CSA C22.2