



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



MRF26ANSWH 6A/3A 120V RF Wireless Switch White

Lutron

Catalog Number	MRF26ANSWH
Manufacturer	Lutron
Description	Maestro Wireless Switch, Incandescent/Halogen, Magnetic Low-Voltage, Electronic Low-Voltage, Non-Dim Fluorescent, Multi-Location/Single-Pole, 120V/6A Light or 3A Fan In White
Weight per unit	0.2500 (lbs/each)
Product Category	Lighting Controls

Features

actuator	Tapswitch
amperage rating	6/3 A
connection	Screw Terminal
Contact Configuration	N-O
Contact Rating	6/3 A
Frequency Range	60Hz
Material	Plastic/Metal
Poles	1 PH
Voltage Rating	ELBOW FITTING, 316 STAINLESS STEEL MATERIAL; 1/2 INCH SIZE A; 1/2 INCH SIZE B; .5 SIZE A - DECIMAL; .5 SIZE B - DECIMAL; 1/2 SIZE A - FRACTIONAL; 1/2 SIZE B - FRACTIONAL; NUCLEAR, PHARMACEUTICAL INDUSTRY CHEMICAL, PETROCHEMICAL APPLICATION; CAST PROCESS
Wattage	720/360 W

Material, Color, and Finish

Color	WHITE GLOSS
-------	-------------

Dimensions and Weight

Size	4.69 in (119 mm) x 9.38 in (239 mm)
------	-------------------------------------

Descriptions

Description	6A/3A 120V RF WIRELESS SWITCH WHITE
Long Description	Maestro Wireless Switch, Incandescent/Halogen, Magnetic Low-Voltage, Electronic Low-Voltage, Non-Dim Fluorescent, Multi-location/single-pole, 120V/6A light or 3A fan in white
Product Type	MRF-FM-6A Switch 120V White
Special Features	Switch with radio frequency receiver



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	Lutron
GTIN	00027557637176
Manufacturers Part Number	MRF2-6ANS-WH
sub brand	Maestro Wireless
UPC	027557637176

Taxonomies, Classifications, and Categories

Category Description	Residential dimmers, motion sensors, controls, & photo cells
Type	Wireless electronic switch, multi-location/single-pole

Availability

Status	Inactive
--------	----------

Packaging

Carton	1
Weight Per each	0.25

Uses, Certifications, and Standards

Application	Lighting Control
Enclosure	Plastic
environmental conditions	0% to 90% humidity, non-condensing. Indoor use only.
Mounting	WALLBOX
Operating Temperature	0-40°C
standard	UL, CSA, FCC, IC, SCT, NOM, CEC (title24)