

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



MS0PS6M2DVWH Maestro DV 6A Occupancy 3WAY White Lutron

October Ni colore	A ACODC (A AOD) WAYLI
Catalog Number	MS0PS6M2DVWH
Manufacturer	Lutron
Description	Occupancy Sensor, 120 to 277 V Ac, 900 to 400 SQ.FT (Major Motion Coverage);82 to 36 M^2 (Minor Motion Coverage)
	Coverage, 1 Min;5 Min;15 Min;30 Min Time Delay, 2-18/16 In
	Length, 4-11/16 In Width, White, 5 Yr Warranty, +32 °F Operating
	Temperature, +104 °F Operating Temperature
Weight per unit	
Product Category	Lighting Occupancy Sensors
eatures	
body	Plastic
load	6 A@120 to 277 VAC lights/3 A@120 VAC fan/3 A@120 VAC light and fan
media	Yes
sensing range	900 ft2 (82 m2) major motion coverage/400 ft2 (36 m2) minor motion coverage
supply voltage	120 to 277
escriptions	
Description	MAESTRO DV 6A OCCUPANCY 3WAY WHITE
extra long description	LUT MS-OPS6M2-DV-WH Maestro Dual Vo
Special Features	Combines a Maestro switch with a passive infrared occupancy
•	sensor. Detects the heat from occupants moving within an area
	to determine whether the space is occupied. Based on the
	feedback from the sensor, the occupancy sensing switch will
	adjust the load accordingly. Passive infrared sensors with
	exclusive Lutron XCT Technology for fine motion detection. 180
	degree sensor field-of-view. Up to 30 ft x 30 ft (9 m x 9 m) [900 ft x (91 m2)] major motion coverage and 20 ft x 20 ft (6 m x 6 m)
	ft2 (81 m2)] major motion coverage and 20 ft x 20 ft (6 m x 6 m) [400 ft2 (36 m2)]
anufacturer Information	
GTIN	00027557984324
UPC	027557984324
ixonomies, Classifications, an	d Categories
Category Description	Residential dimmers, motion sensors, controls, & photo cells
Туре	Occupancy sensor switch, multi-location/3-way/single-pole,

dual-voltage



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

 ick	١a	yı	•••	y

Carton	1	
Weight Per each	0.25	

Uses, Certifications, and Standards

Enclosure	Plastic
environmental conditions	0 to 90% humidity, non-condensing. Indoor use only.
Mounting	WALLBOX
Operating Temperature	32 to 104
standard	UL, cUL, NOM