

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



#### N1.0 1/0 Cu Split Bolt Nsi Industries

Soon	
Catalog Number	N1.0
Manufacturer	Nsi Industries
Description	Copper Split Bolt Connector 1/0 Awg Copper Split Bolt Connectors Are High-Strength Solderless Service Connectors Made Of High-Copper Alloy For Copper and Copperweld Wires. Type For Two Maximum Wire Sizes.
Weight per unit	0.1600 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
Material	Copper
Number of Conductors	2
Poles	1
Voltage Rating	
Warranty	1 YEAR
Wire Size	4.00L 4.00TD
Wire Type	Class A & B
Material, Color, and Finish	
Color	Copper
Finish	COPPER
<b>Dimensions and Weight</b>	
Size	L=1.417 - W=.787
Descriptions	
Description	1/0 CU SPLIT BOLT
extra long description	NSI N-1/0 Copper Split Bolt 1/0
Features	Copper Split Bolt Connector 1/0 AWG Copper Split Bolt Connectors are high-strength solderless service connectors made of high-copper alloy for copper and copperweld wires. Type for two maximum wire sizes.
Long Description	Copper Split Bolt Connector 1/0 AWG Copper Split Bolt Connectors are high-strength solderless service connectors made of high-copper alloy for copper and copperweld wires. Type for two maximum wire sizes.
Product Type	Copper Split Bolt 1/0
Special Features	4 SOL-1/0 STR - 20 Pack



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

V	lanufac	turer In	forma	tion
---	---------	----------	-------	------

Brand	NSi	
GTIN	00662381020062	
Manufacturers Part Number	N-1/0	
UPC	662381020062	

## **Taxonomies, Classifications, and Categories**

Category Description	SPLIT BOLTS
Туре	Copper Split Bolts

## **Availability**

•		
Status	Inactive	
Jiaius		

### **Packaging**

Carton	1
Weight Per each	0.16

### Uses, Certifications, and Standards

Application	Wire Termination
environmental conditions	90 C
standard	UL486B
Temperature Rating	90 C