

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



N250 250 Cu Split Bolt Nsi Industries

Catalan Numban	Noto
Catalog Number Manufacturer	N250 Nsi Industries
Description	Split Bolt Connector, #1/0 Awg (Range Of Equal Main and
Description	Tap-Solid) Conductor Size, 250 MCM (Range Of Equal Main and
	Tap-Stranded);1/0 Awg (Minimum Tap With One Maximum
	Main-Stranded) Conductor Size, Non-Insulated,
	Copper;Copperweld Conductor Material, 2 Conductors, +90 °C
	Operating Temperature, 2.106 In Overall Length, Split Terminal,
	600 V, 0.53 LB/Ea
Weight per unit	0.5300 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
Material	Copper
Number of Conductors	2
Poles	1
Voltage Rating	
Warranty	
Wire Size	
Wire Type	Class A & B
Material, Color, and Finish	
Color	Copper
Finish	COPPER
Dimensions and Weight	
Size	L=2.106 - W=1.102
Descriptions	
Description	250 CU SPLIT BOLT
extra long description	NSI N-250 Copper Split Bolt 750 Tin
Features	Copper Split Bolt Connector 250 MCM Copper Split Bolt
	Connectors are high-strength solderless service connectors made
	of high-copper alloy for copper and copperweld wires. Type for
	two maximum wire sizes.
Manufacturer Information	
GTIN	00662381020093
LIDO	//220102002

Ma

GTIN	00662381020093
UPC	662381020093

Taxonomies, Classifications, and Categories

Category Description	SPLIT BOLTS
Туре	Copper Split Bolts



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Pac	kag	ın	g

Carton	1	
Package	6	
Weight Per each	0.53	

Uses, Certifications, and Standards

Application	Wire Termination
environmental conditions	90 C
standard	UL486B
Temperature Rating	90 C