


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





N2S2210 Cor-Resist PB Station

Crouse-Hinds

Catalog Number	N2S2210
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series N2S Pushbutton Control Station, With Pushbuttons, With One 3/4" Hub, Krydon Fiberglass-Reinforced Polyester, Single-Gang, 2, Dead End, 3/4"
Weight per unit	2.9 (lbs/each)
Product Category	Control Station Complete Assem

Features

action	Momentary
dimensions	6.0000 IN X 6.0000 IN X 11.2000 IN
Material	Krydon fiberglass-reinforced polyester
Voltage Rating	600 VAC

Dimensions and Weight

Size	3-	-1	3/	/1	6 I	n	Wid	dth	١X	5-	-3/	4 I	n l	Dei	oth	X	7-1	/4	In	Heig	ht	

Descriptions

Description	COR-RESIST PB STATION
extra long description	CRS-H N2S2210 FS COR RESIS CNTRL ST
Features	Crouse-Hinds series N2S and N2SC non-metallic pushbutton control stations and selector switches are used in conjunction with magnetic starters or contactors for remote control of motors. N2S and N2SC pilot lights are used to visually indicate at a remote location that the desired function is being performed.
Long Description	Eaton Crouse-Hinds series N2S pushbutton control station, With pushbuttons, With one 3/4" hub, Krydon fiberglass-reinforced polyester, Single-gang, 2, Dead end, 3/4"
Product Type	FS Cor Resis CNTRL Stations
Special Features	Number of Unit 2, Contact Configuration 2 No-2 Nc

Manufacturer Information

Brand	Eaton	
GTIN	00782274802503	
Manufacturers Part Number	N2S2210	
UPC	782274802503	

Taxonomies, Classifications, and Categories

Category Description	STANDARD DUTY PUSHBUTTONS (10250H-)
Туре	Pushbutton control station



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Pa		

Carton	1	
Weight Per each	2.9	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
Enclosure	Class I Div 2 Group B C D, NEMA 3/4X/7B/7C/7D/12
standard	UL 1203, CSA C22.2