CONNECTORS

Split Bolt Connectors

Copper Tin Plated With Spacer Dual Rated Split Bolts

N-SP Series

LISTED

SPECIFICATIONS

- UL486A/B Listed Wire Connector.
- UL486D Listed Direct Bury.

FEATURES

- Aluminum to copper (Dual Rated).
- Aluminum to aluminum.
- Steel to aluminum.
- Copper to copper.
- Steel to copper.
- Electro-tinned body.
- UL listed for copper and copperweld wires only.
- Includes nut, spacer and pressure pad.

CAT. NO.	CONDUCTOR RANGE OF EQUAL MAIN & TAP MIN.	CONDUCTOR RANGE OF EQUAL MAIN & TAP MAX.	MIN. TAP WITH ONE MAX. MAIN	ACSR RANGE OF MAIN OR TAP MIN.	ACSR RANGE OF MAIN OR TAP MAX.	WIRE DIA. RANGE IN.	REC. TORQUE (IN. LB.)	STD. CTN. QTY.
N-6SP	14 STR	8 STR	14 STR	–	8	0.073 - 0.146	165	100
N-4SP	10 STR	6 STR	10 SOL	–	6	0.116 – 0.184	165	75
N-3SP	8 SOL	3 STR	8 SOL	6	4	0.128 – 0.258	275	50
N-2SP	8 SOL	2 STR	8 SOL	6	2	0.128 – 0.316	275	40
N-1/0SP	6 SOL	1/0 STR	10 SOL	6	1	0.162 – 0.375	385	20
N-2/0SP	6 STR	2/0 STR	10 SOL	6	1/0	0.184 – 0.419	385	15
N-3/0SP	4 STR	3/0 STR	6 SOL	6	2/0	0.198 – 0.470	500	10
N-250SP	4 STR	250 MCM	4 STR	4	4/0	0.232 – 0.575	650	6
N-350SP	3/0 STR	350 MCM	1 SOL	2/0	350	–	650	4
N-500SP	3/0 STR	500 MCM	1/0 STR	2/0	477 18/1	–	825	3
N-750SP	250 MCM	750 MCM	2/0 STR	4/0	666.6	–	1000	2
N-1000SP	250 MCM	1000 MCM	4/0 STR	300	900	–	1100	2

CONNECTORS

Split Bolt Connectors

Copper Tin Plated With Spacer Dual Rated Split Bolts

N-SP Series

LISTED

SPECIFICATIONS

- UL486A/B Listed Wire Connector.
- UL486D Listed Direct Bury.

FEATURES

- Aluminum to copper (Dual Rated).
- Aluminum to aluminum.
- Steel to aluminum.
- Copper to copper.
- Steel to copper.
- Electro-tinned body.
- UL listed for copper and copperweld wires only.
- Includes nut, spacer and pressure pad.

CAT. NO.	CONDUCTOR RANGE OF EQUAL MAIN & TAP MIN.	CONDUCTOR RANGE OF EQUAL MAIN & TAP MAX.	MIN. TAP WITH ONE MAX. MAIN	ACSR RANGE OF MAIN OR TAP MIN.	ACSR RANGE OF MAIN OR TAP MAX.	WIRE DIA. RANGE IN.	REC. TORQUE (IN. LB.)	STD. CTN. QTY.
N-6SP	14 STR	8 STR	14 STR	–	8	0.073 - 0.146	165	100
N-4SP	10 STR	6 STR	10 SOL	–	6	0.116 – 0.184	165	75
N-3SP	8 SOL	3 STR	8 SOL	6	4	0.128 – 0.258	275	50
N-2SP	8 SOL	2 STR	8 SOL	6	2	0.128 – 0.316	275	40
N-1/0SP	6 SOL	1/0 STR	10 SOL	6	1	0.162 – 0.375	385	20
N-2/0SP	6 STR	2/0 STR	10 SOL	6	1/0	0.184 – 0.419	385	15
N-3/0SP	4 STR	3/0 STR	6 SOL	6	2/0	0.198 – 0.470	500	10
N-250SP	4 STR	250 MCM	4 STR	4	4/0	0.232 – 0.575	650	6
N-350SP	3/0 STR	350 MCM	1 SOL	2/0	350	–	650	4
N-500SP	3/0 STR	500 MCM	1/0 STR	2/0	477 18/1	–	825	3
N-750SP	250 MCM	750 MCM	2/0 STR	4/0	666.6	–	1000	2
N-1000SP	250 MCM	1000 MCM	4/0 STR	300	900	–	1100	2