

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



N3 #3 Cu Split Bolt Nsi Industries

Catalog Number	N3					
Manufacturer	Nsi Industries					
Description	Copper Split Bolt Connector 3 Awg Copper Split Bolt Connectors Are High-Strength Solderless Service Connectors Made Of High-Copper Alloy For Copper and Copperweld Wires. Type For Two Maximum Wire Sizes.					
Weight per unit	0.1000 (lbs/each)					
Product Category	Large Terminals & Connectors					
Features						
Material	Copper					
Number of Conductors	2					
Poles	1					
Voltage Rating	600 V					
Warranty	1 YEAR					
Wire Size	6 SOL - 2 SOL					
Wire Type	Class A & B					
Material, Color, and Finish						
Color	Copper					
Finish	COPPER					
Dimensions and Weight						
Size	L=1.153 - W=.748					
Descriptions						
Description	#3 CU SPLIT BOLT					
extra long description	NSI N-3 Copper Split Bolt 2 3 wire					
Features	Copper Split Bolt Connector 3 AWG Copper Split Bolt Connectors are high-strength solderless service connectors made of high-copper alloy for copper and copperweld wires. Type for two maximum wire sizes.					
Long Description	Copper Split Bolt Connector 3 AWG Copper Split Bolt Connectors are high-strength solderless service connectors made of high-copper alloy for copper and copperweld wires. Type for two maximum wire sizes.					
Product Type	Copper Split Bolt 2 3 Wire					
Special Features	6 SOL-2 SOL - 50 Pack					



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и		_		1		_ 1				.					_
ľ	۱ <i>۱</i>	12	n		-	СТ		·Δr	ın	TO	۱rr	ทว	TI	n	7
	v			u	а	L.I	uı	CI	'In	H.V.	,, ,	па		u	

Brand	NSi
GTIN	00662381020048
UPC	662381020048

Taxonomies, Classifications, and Categories

Category Description	SPLIT BOLTS
Туре	Copper Split Bolts

Packaging

magg		
Carton	1	
Package	50	
Weight Per each	0.1	

Uses, Certifications, and Standards

Application	Wire Termination
environmental conditions	90 C
standard	UL486B
Temperature Rating	90 C