

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





N30 3/0 Cu Split Bolt Nsi Industries

Catalog Number	N30				
Manufacturer	Nsi Industries				
Description	Copper Split Bolt Connector 3/0 Awg Copper Split Bolt Connectors Are High-Strength Solderless Service Connectors Made Of High-Copper Alloy For Copper and Copperweld Wires. Type For Two Maximum Wire Sizes.				
Weight per unit	0.4300 (lbs/each)				
Product Category	Large Terminals & Connectors				
Features					
Material	Copper				
Number of Conductors	2				
Poles	1				
Voltage Rating					
Warranty	1 YEAR				
Wire Size	2 SOL - 3/0 STR				
Wire Type	Class A & B				
Material, Color, and Finish					
Color	Copper				
Finish	COPPER				
Dimensions and Weight					
Size	L=2.007 - W=1.102				
Descriptions					
Description	3/0 CU SPLIT BOLT				
extra long description	NSI N-3/0 Copper Split Bolt 2 Tin P				
Features	Copper Split Bolt Connector 3/0 AWG Copper Split Bolt Connectors are high-strength solderless service connectors made of high-copper alloy for copper and copperweld wires. Type for two maximum wire sizes.				
Long Description	Copper Split Bolt Connector 3/0 AWG Copper Split Bolt Connectors are high-strength solderless service connectors made of high-copper alloy for copper and copperweld wires. Type for two maximum wire sizes.				
Product Type	Copper Split Bolt 2 Tin Plated				
Special Features	2 SOL-3/0 STR - 10 Pack				



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и		_		1		_ 1				.					_
ľ	۱ <i>۱</i>	12	n		-	СТ		·Δr	ın	TO	۱rr	ทว	TI	n	7
	v			u	а	L.I	uı	CI	'In	H.V.	,, ,	па		u	

Brand	NSi
GTIN	00662381020086
Manufacturers Part Number	N-3/0
UPC	662381020086

Taxonomies, Classifications, and Categories

Category Description	SPLIT BOLTS
Туре	Copper Split Bolts

Packaging

J		
Carton	1	
Package	10	
Weight Per each	0.43	

Uses, Certifications, and Standards

Application	Wire Termination
environmental conditions	90 C
standard	UL486A
Temperature Rating	90 C