

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

N4 #4 Cu Split Bolt Nsi Industries

| Catalog Number | N4 |
|---|--|
| Manufacturer | Nsi Industries |
| Description | Split Bolt Connector, #8 Awg (Range Of Equal Main and Tap-Solid Conductor Size, #4 Awg (Range Of Equal Main and Tap-Stranded);#16 Awg (Minimum Tap With One Maximum Main-Stranded) Conductor Size, Non-Insulated, Copper;Copperweld Conductor Material, 2 Conductors, +90 °C Operating Temperature, 1.153 In Overall Length, Split Terminal, 600 V, 0.08 LB/Ea |
| Weight per unit | 0.0800 (lbs/each) |
| Product Category | Large Terminals & Connectors |
| Features | |
| Material | Copper |
| Number of Conductors | 2 |
| Poles | 1 |
| Voltage Rating | 600 V |
| Warranty | 1 YEAR |
| Wire Size | 8 SOL - 4 SOL |
| Wire Type | Class A & B |
| Material, Color, and Finish | |
| Color | Copper |
| Finish | COPPER |
| Dimensions and Weight | |
| Size | L=1.153 - W=.748 |
| Descriptions | |
| Description | #4 CU SPLIT BOLT |
| extra long description | NSI N-4 Copper Split Bolt 3 3 wire |
| Features | Copper Split Bolt Connector 4 AWG Copper Split Bolt Connectors |
| | are high-strength solderless service connectors made of |
| | high-copper alloy for copper and copperweld wires. Type for two |
| | maximum wire sizes. |
| Manufacturer Information | |
| GTIN | 00662381020031 |
| UPC | 662381020031 |
| Taxonomies, Classifications, and Category Description | l Categories SPLIT BOLTS |
| _ | |

Copper Split Bolts



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging |
|-----------|
|-----------|

| Carton | 1 |
|-----------------|----|
| Package | 75 |
| Weight Per each | |

Uses, Certifications, and Standards

| Application | Wire Termination |
|--------------------------|------------------|
| environmental conditions | 90 C |
| standard | UL486B |
| Temperature Rating | 90 C |