

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



N6SP #6 Al-Cu Split Bolt *Nsi Industries*

Catalog Number	N6SP
Manufacturer	Nsi Industries
Description	All Purpose Split Bolt Connector 6 Awg Is Used For Combinations
	Of Aluminum to Copper, Aluminum to Aluminum, Steel to
	Aluminum, Copper to Copper, and Steel to Copper Applications.
	They Have An Electro-Tinned Body. UI Listed For Copper and
	Copperweld Wires Only. Includes Nut, Spacer and Pressure Pad.
Weight per unit	0.0600 (lbs/each)
Product Category	Large Terminals & Connectors

Features

Copper
2
1
600 V
1 YEAR
14 STR - 8 STR
Class A & B

Material, Color, and Finish

Color	Tin Plated Copper
Finish	Tin Plated Copper

Dimensions and Weight

	J e e e e e e e e e e e e e e e e e e e
Size	L=1.062 - W=.492

Descriptions

#6 AL-CU SPLIT BOLT
NSI N-6SP Copper Split Bolt 6
All Purpose Split Bolt Connector 6 AWG: All Purpose Split Bolt Connectors are used for combinations of aluminum to copper, aluminum to aluminum, steel to aluminum, copper to copper, and steel to copper applications. They have an electro-tinned body. UL listed for copper and copperweld wires only. Includes nut, spacer and pressure pad.
All Purpose Split Bolt Connector 6 AWG is used for combinations of aluminum to copper, aluminum to aluminum, steel to aluminum, copper to copper, and steel to copper applications. They have an electro-tinned body. UL listed for copper and copperweld wires only. Includes nut, spacer and pressure pad.
Copper Split Bolt 6
14 STR-8 STR - 100 Pack



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	NSi	
GTIN	00662381020321	
Manufacturers Part Number	N-6SP	
UPC	662381020321	

Taxonomies, Classifications, and Categories

Category Description	SPLIT BOLTS
Type	Tin Plated Copper Split Bolt

Packaging

Carton	1	
Weight Per each	0.06	

Uses, Certifications, and Standards

Application	Wire Termination
environmental conditions	90 C
standard	UL486B
Temperature Rating	90 C