



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3700 Pasadena Fwy
77503-0000, TX Pasadena
Phone: 281-220-3780
Fax: 713-740-6104



NNC37X37WH2 37MX37MMX2M WH Wire DCT Panduit Corporation

Catalog Number	NNC37X37WH2
Manufacturer	Panduit Corporation
Description	The NNC37X37WH2 Halogen-Free Wide Slot Wiring Duct Is Used to Route, Protect, and Manage Wires Near Sensitive Electronic Equipment and In Environments Where Heat Resistance or Public Safety Is A Concern. UL 94 Flame Class Of V-0 With A UL Recognized Continuous-Use Temperature Up to 95°C (203°F). Halogen-Free, Polyphenylene Oxide (Ppo). Mounting Holes Provided. 1.41" X 1.46" (35.8 MM X 37.1 MM) and 6.6' (2 M) Long. Cover Included. Color White. 5 Pieces Per Package.
Weight per unit	1.5 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

Features

connection	DIN Standard Mounting Holes
media	Yes

Material, Color, and Finish

Color	White
-------	-------

Dimensions and Weight

Length	NA
Size	1.46 x 1.41
Width	1.46

Descriptions

Description	37MX37MMX2M WH WIRE DCT
extra long description	PAN NNC37X37WH2 Panduct® NNC37X37WH
Long Description	The NNC37X37WH2 Halogen-Free Wide Slot Wiring Duct is used to route, protect, and manage wires near sensitive electronic equipment and in environments where heat resistance or public safety is a concern. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 95°C (203°F). Halogen-Free, Polyphenylene Oxide (PPO). Mounting holes provided. 1.41" x 1.46" (35.8 mm x 37.1 mm) and 6.6' (2 m) long. Cover included. Color White. 5 pieces per package.
Product Type	Panduct® NNC37X37WH2 Wide Slot Duct, White, Hal-Free Ppo, 1.



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3700 Pasadena Fwy
77503-0000, TX Pasadena
Phone: 281-220-3780
Fax: 713-740-6104

Manufacturer Information

Brand	PANDUIT
GTIN	00074983442775
Manufacturers Part Number	NNC37X37WH2
UPC	074983442775

Taxonomies, Classifications, and Categories

Category Description	Panduit & Wiremold Metallic & Non-Metallic Raceways
Type	Wiring Duct Base with Cover

Packaging

Carton	1
Package	20
Weight Per meter	1.47

Uses, Certifications, and Standards

Application	NNC Wiring Duct is Used to Route, Protect, and Manage Wires near Sensitive Electronic Equipment and in Environments where Heat Resistance or Public Safety is a Concern
standard	RoHS Compliant, UL Recognized, CE Compliant, DIN 43659 Compliant, EN45545-2 HL1 & HL3 Compliant, BABA Compliant