

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## NPDB14201 PDB 1 Pole, Line 1X2/0-14, Load 4X4-14 Nsi Industries

Catalog Number	NPDB14201		
Manufacturer	Nsi Industries		
Description	100KA Short Circuit Current Rated Power Distribution Block. 1 X 2/0-14 Awg Line, 4 X 4-14 Awg Load Power Distribution Blocks Are Made Of Valox Nylon 6/6, Finger Safe Lexan 500R Polycarbonate Panels and Covers, High-Conductivity 6061-T6 Electro-Tin Plated Aluminum Alloy Connector. Each Block Can Stand Alone or Combine With Other Blocks to Form A Multi-Block Set, and Are Also Din Rail Mountable With Built In Locking Mechanism to Lock/Release.		
Weight per unit	0.2760 (lbs/each)		
Product Category	Power BLKS & Distribution BLKS		
Features			
amperage rating	175A		
Material	6061-T6 Aluminum Body - Valox Nylon 6/6 Base - Lexan 500R Polycarbonate Panels and Covers		
Number of Terminals	5		
Voltage Rating	600		
Warranty	1 YEAR		
Wire Size	(1) 2/0-14 AWG(Line) - (4) 4-14 AWG(Load)		
Material, Color, and Finish Color	Black Base-Clear Panels and Covers		
Dimensions and Weight Size	L=3.560 - W=1.020 - H=2.570		
Size	L=3.30U - VV=1.U2U - H=2.37U		



## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

				•	
11	nc	cri	nt	$\mathbf{I}$	nc
.,		L-I I	.,.		

Descriptions				
Description	PDB 1 POLE, LINE 1X2/0-14, LOAD 4X4-14			
extra long description	NSI NPDB-14-2/0-1 NPDB LINE 1X2/0-1			
Features	100kA Short Circuit Current Rated Power Distribution Block. 1 x 2/0-14 AWG Line, 4 x 4-14 AWG Load Power Distribution Blocks are made of Valox Nylon 6/6, Finger Safe Lexan 500R Polycarbonate Panels and Covers, high-conductivity 6061-T6 Electro-Tin Plated aluminum alloy connector. Each block can stand alone or combine with other blocks to form a multi-block set, and are also Din Rail Mountable with built in locking mechanism to lock/release.			
Long Description	100kA Short Circuit Current Rated Power Distribution Block. 1 x 2/0-14 AWG Line, 4 x 4-14 AWG Load Power Distribution Blocks are made of Valox Nylon 6/6, Finger Safe Lexan 500R Polycarbonate Panels and Covers, high-conductivity 6061-T6 Electro-Tin Plated aluminum alloy connector. Each block can stand alone or combine with other blocks to form a multi-block set, and are also Din Rail Mountable with built in locking mechanism to lock/release.			
Product Type	NPDB Line 1X2/0-14 - Load 4X4-14			
Special Features	100kA Short Circuit Current Rated (SCCR), Din Rail Mount with Locking Mechanism to lock/release block on Din Rail, Multi Pole Ganging, Finger Safe Lexan 500R Polycarbonate Panels & Covers			
Manufacturer Information				
Brand	NSi			
GTIN	00662381367501			
Manufacturers Part Number	NPDB-14-2/0-1			
UPC	662381367501			
Taxonomies, Classifications, and Cate	egories			
Category Description	•			
Туре	Circula Duina and (Lina) Circula Caranadam (Land)			
Packaging				
Carton	1			
Weight Per each	0.276			
Uses, Certifications, and Standards				
Application	NSI			
Mounting	Slotted Holes in Base, 35mm DIN Rail w/Locking Feature			
standard	UL1953 and UL1059 Listed, cULus			
standard	OL 1953 and OL 1059 Listed, COLUS			