

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



P518809 Pendant Bruched Nickel *Progress Lighting*

P518809		
Progress Lighting		
Add Focused Task Lighting Packed With Industrial Flair With The Fresnel Lens Collection Brushed Nickel One-Light Industrial Hanging Pendant Light. A Fresnel Glass Lens Composed Of High-Quality Prismatic Glass Adds to The Pendant'S Historical Aesthetic. The Antique-Style Hinge-Locking Nautical Design Allows For Easy Bulb Changes and Stress-Free Maintenance. An Understated Brushed Nickel Finish Coats The Light Fixture to Accentuate The Pendant'S Antique Nautical Style. The Light Fixture'S Industrial Design I		
8.2 (lbs/each)		
Incandescent Suspended Archite		
plated		
Indoor		
A19		
1		
36		
Hardwired		
socket		
120 V		
100		
Nickel		
steel		
Traditional/Classic		
10.5		
12.125		
12.125		



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Desc	rıp	tioi	ns

Description	PENDANT BRUCHED NICKEL
extra long description	PROG P5188-09 P5188-09 1-100W MED P
Long Description	Add focused task lighting packed with industrial flair with the Fresnel Lens Collection Brushed Nickel One-Light Industrial Hanging Pendant Light. A Fresnel glass lens composed of high-quality prismatic glass adds to the pendant's historical aesthetic. The antique-style hinge-locking nautical design allows for easy bulb changes and stress-free maintenance. An
	understated brushed nickel finish coats the light fixture to accentuate the pendant's antique nautical style. The light fixture's industrial design i
Product Type	P5188-09 1-100W Med Pendant

Manufacturer Information

Brand	Progress Lighting	
GTIN	00785247163984	
Manufacturers Part Number	P5188-09	
UPC	785247163984	

Taxonomies, Classifications, and Categories

Туре	PENDANT	
Packaging		
Carton	1	

8.16

Weight Per each Uses, Certifications, and Standards

Mounting	Ceiling Stem Hung With 6 Links Of Chain
standard	UL-CUL