

## ELLIOT ELECTRIC SUPPLY Mar Deliver Cost Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## PLT2SM0 7.4" 50LB BLK LCK CBL Tie Panduit Corporation

Catalog Number	PLT2SM0
Manufacturer	Panduit Corporation
Description	Panduit Corporation Panduit PLT2S-M0 Locking Cable Ties Are Designed to Satisfy The Needs Of General Applications, While Delivering Consistent Performance and Reliability. Featuring A Curved Tip to Allow For Easy Pick Up From Flat Surfaces and Faster Initial Threading. Standard Cross Section, 7.4" (188MM) Length. For Indoor/Outdoor Use, Made Of Weather Resistant Nylon 6.6, Are Black In Color and Come In Packages Of 1000.
Weight per unit	C C
Product Category	Cable Ties & Wraps
Features	
media	Yes
Tensile Strength	50
Dimensions and Weight	
Length	7.4
Thickness	0.06
Descriptions	
Description	7.4" 50LB BLK LCK CBL TIE
extra long description	PAN PLT2S-M0 Pan-Ty® PLT2S-M0 Cable
Long Description	Panduit PLT2S-M0 Locking Cable Ties are designed to satisfy the needs of general applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Standard cross section, 7.4" (188mm) length. For Indoor/Outdoo use, made of Weather Resistant Nylon 6.6, are black in color and come in packages of 1000.
Product Type	Pan-Ty® PLT2S-M0 Cable Tie, Black, Uv PA6.6, 7.4"L, 50LB, PK
Special Features	Indoor/Outdoor
Manufacturer Information	
Brand	Panduit®
GTIN	00074983540792
Manufacturers Part Number	PLT2S-M0
UPC	074983540792
Taxonomies, Classifications, and C Type	Categories Premium Cable Tie



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Availability

minimum qty	1000
Packaging	
Carton	1000
Package	5000
Weight Per each	3.215
Uses, Certifications, and Standards	
standard	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant

CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Compliant