ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

PRST2 3/4" PLASTIBOND HUB

ROBROY/PLASTI-BOND

Catalog Number	PRST2
Manufacturer	ROBROY/PLASTI-BOND
Description	3/4 KNOCKOUT HUB
Weight per unit	0.3000 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

Material	2 Mil Red Urethane Coated Interior/40 Mil Gray PVC Coated Exterior Ferrous Metal

Dimensions and Weight

Size	2.25 Inch Diameter

Descriptions

Additional Information	Seal Type O-Ring Gasket; Wall Thickness 0.19 Inch; Enclosure Type Class I Div 2, Class II/III-Div 1 and 2; Applicable Standard ISO 9001
Commodity Description	Rigid Conduit Fittings - Steel
Description	3/4" PLASTIBOND HUB
Long Description	3/4 KNOCKOUT HUB KNOCKOUT HUB, 2 MIL RED URETHANE COATED INTERIOR/40 MIL GRAY PVC COATED EXTERIOR FERROUS METAL MATERIAL; 2.25 INCH DIAMETER SIZE; RIGID CONDUIT USED ON; UL (CANADA AND US), UL 514B, ETL APPROVAL; 3/4 INCH TRADE SIZE; CHEMICAL RESISTANT; REDH2OT[R] BRAND
Product Type	Knockout Hub
Extra Long Description	2 MIL RED URETHANE (INTERIOR)/40 MIL GRAY PVC COATED (EXTERIOR) FERROUS METAL MATERIAL; 2.25 INCH DIAMETER SIZE; ST STYLE CONDUIT USED ON; UL (CANADA AND US), UL 514B APPROVAL; 3/4 INCH TRADE SIZE; NEMA 2/3/3R/4/4X/11/12; MAXIMUM WALL THICKNESS 0.19 INCH; SEAL TYPE O-RING GASKET; ENCLOSURE RATING CLASS I DIV 2, CLASS II DIV 1 AND 2, CLASS III DIV 1 AND 2; APPLICABLE STANDARD ISO 9001, NEC/CEC; ST MODEL

Manufacturer Information

Brand	PLASTI-BOND REDH2OT[R] PLASTIBOND
GTIN	00784011207374
Manufacturers Part Number	PRST2
UPC	889953

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

Taxonomies, Classifications, and Categories

Category Description	ALL PLASTIBOND FITTINGS

Trade Size

Trade Size	3/4 INCH

Availability

Manufacturer Status	Non-Stock

Packaging

Carton	1
Package	25
Weight Per Each	0.3000 (lbs/each)

Uses, Certifications, and Standards

Approval	UL (Canada and US), UL 514B, ETL
Used On	RIGID CONDUIT