

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UPC

PSG240E PWR Supply-1PH 85-264VAC 24VDC@10a Eaton Corp

Eaton corp	
Catalog Number	PSG240E
Manufacturer	Eaton Corp
Description	Power Supply, 240W, Single-Phase, 100-240V Input Voltage, 24 VDC ± 2% Output Voltage, 2.9A Input Current, 10A Output Current, 47-63 HZ, 85-264V, 120-375 VDC, Aluminum Enclosure, Heavy-Duty Screw Terminals
Weight per unit	
Product Category	Ac Power Supplies
Features	
dimensions	4.7600 IN X 3.3500 IN X 4.6700 IN
Material	Aluminum
media	Yes
Phase	Single-phase
Voltage Rating	85-264 Vac, 100-375 Vdc
Wattage	240W
Descriptions	
Description	POWER SUPPLY-1PH 85-264VAC, 24VDC@10A
extra long description	ETN PSG240E POWER SUPPLY-1PH 85-264
Features	Eaton's PSL general purpose power supplies are single-phase, low-profile and can be mounted on standard DIN rail. The devices offer IEC Class II double insulated protection, which means that no earth connection is required, resulting in low leakage current and a longer lifespan. PSL power supplies are designed for use in compact cabinets for home automation, panel shops, food and beverage, and HVAC applications, communication networks and sensors.
Long Description	Power Supply, 240W, Single-phase, 100-240V input voltage, 24 Vdc ± 2% output voltage, 2.9A input current, 10A output current, 47-63 Hz, 85-264V, 120-375 Vdc, Aluminum enclosure, Heavy-duty screw terminals
Product Type	Power Supply-1PH 85-264VAC, 24VDC@10a
Special Features	Varistor transient surge voltage, surge voltage protection against internal surge, safety class 1 with ground connection, finger-safe cover
Manufacturer Information	
Brand	EATON CUTLER-HAMMER
GTIN	00786685215464
Manufacturers Part Number	PSG240E

786685215464



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Ca	U
Category Description	POWER SUPPLIES
Туре	Low-profile power supply
Availability	
Status	Inactive
Packaging	
Carton	1
Weight Per each	2.63
Uses, Certifications, and Standards	
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels and EOEMs
Frequency Rating	47-63 Hz
standard	IEC Rated,EN Listed,cULus/UL 60950-1,CSA Certified,UL 508,cUL Certified,CE Marked,RoHS Compliant,German Safety