



PTS250 Pin Reducer

Nsi Industries

Catalog Number	PTS250
Manufacturer	Nsi Industries
Description	Solid Pin Terminal For Copper and Aluminum Conductors 250 MCM All-Aluminum Pin Terminals Is Designed For Termination Of Both Aluminum and Copper Conductors. The Solid Pin Is Made Of Aluminum and Is Tin-Plated and Pre-Filled With Oxide Inhibitor. A Cover Is Provided For Quick Installation. Rated 600 Volts.
Weight per unit	0.1600 (lbs/each)
Product Category	Large Terminals & Connectors

Features

connection	3/0 Pin
insulation	Plastisol Cover
Material	Aluminum
Number of Conductors	1
Poles	1
Voltage Rating	600 V
Warranty	1 YEAR

Material, Color, and Finish

Color	Brown
Finish	Tin Plated

Dimensions and Weight

Size	L=2.62 - OD=1.09 - ID=.594 - Pin Dia=.460
------	---

Descriptions

Description	PIN REDUCER
extra long description	NSI PTS250 Aluminum Pin Terminal Al
Features	Solid Pin Terminal for Copper and Aluminum Conductors 250 MCM All-aluminum Pin Terminals is designed for termination of both aluminum and copper conductors. The solid pin is made of aluminum and is tin-plated and pre-filled with oxide inhibitor. A cover is provided for quick installation. Rated 600 Volts.
Long Description	Solid Pin Terminal for Copper and Aluminum Conductors 250 MCM All-aluminum Pin Terminals is designed for termination of both aluminum and copper conductors. The solid pin is made of aluminum and is tin-plated and pre-filled with oxide inhibitor. A cover is provided for quick installation. Rated 600 Volts.
Product Type	Aluminum Pin Terminal Al Pin 250 MCM
Special Features	250 MCM (STR) - 3/0 Pin Size



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

5018 W Main Street
74701-0000, OK Durant
Phone: 580-745-5448
Fax: 580-745-5449

Manufacturer Information

Brand	NSi
GTIN	00662381033482
Manufacturers Part Number	PTS250
UPC	662381033482

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	Solid Pin

Packaging

Carton	1
Weight Per each	0.16

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486
Temperature Rating	90 C