Eaton QCR1020

Catalog Number: QCR1020

Eaton Quicklag Type QCR 1/2-inch Industrial Thermal-Magnetic Circuit Breaker,Industrial circuit breaker,20 A,10 kAIC,Single-pole,120/240 V,Thermal-magnetic,Cable-in/cable-out,QCR,Non-interchangeable

General specifications

Product Name

Eaton QCR thermal magnetic circuit

breaker

Catalog Number

QCR1020

UPC

786679144060

Product Length/Depth Product Height

4.7 in 1.2 in

Product Width Product Weight

3.1 in 0.2 lb

Warranty Compliances
1 year HACR Rated

Certifications Catalog Notes

UL Listed Standard breaker terminals are box type
CSA Certified lugs. Switching duty rated for fluorescent

lighting applications.





Physical Attributes

Circuit breaker type

QCR

Connection

Cable-in/cable-out

Mounting Method

Rear

Number of poles

Single-pole

Type

Industrial circuit breaker

Performance Ratings

Amperage Rating

20 A

Interrupt rating

10 kAIC

Trip Type

Thermal-magnetic

Voltage rating

120/240 V

Miscellaneous

Options

Non-interchangeable

Resources

Brochures

Loadcenters and Circuit Breakers

Catalogs

Eaton's Volume 4—Circuit Protection

Specifications and datasheets

Eaton Specification Sheet - QCR1020

Circuit Breaker Time/Current Curves For QUICKLAG. Industrial Circuit

Breakers



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia

Eaton QCR1020

Catalog Number: QCR1020

Eaton Quicklag Type QCR 1/2-inch Industrial Thermal-Magnetic Circuit Breaker,Industrial circuit breaker,20 A,10 kAIC,Single-pole,120/240 V,Thermal-magnetic,Cable-in/cable-out,QCR,Non-interchangeable

General specifications

Product Name

Eaton QCR thermal magnetic circuit

breaker

Catalog Number

QCR1020

UPC

786679144060

Product Length/Depth Product Height

4.7 in 1.2 in

Product Width Product Weight

3.1 in 0.2 lb

Warranty Compliances
1 year HACR Rated

Certifications Catalog Notes

UL Listed Standard breaker terminals are box type
CSA Certified lugs. Switching duty rated for fluorescent

lighting applications.





Physical Attributes

Circuit breaker type

QCR

Connection

Cable-in/cable-out

Mounting Method

Rear

Number of poles

Single-pole

Type

Industrial circuit breaker

Performance Ratings

Amperage Rating

20 A

Interrupt rating

10 kAIC

Trip Type

Thermal-magnetic

Voltage rating

120/240 V

Miscellaneous

Options

Non-interchangeable

Resources

Brochures

Loadcenters and Circuit Breakers

Catalogs

Eaton's Volume 4—Circuit Protection

Specifications and datasheets

Eaton Specification Sheet - QCR1020

Circuit Breaker Time/Current Curves For QUICKLAG. Industrial Circuit

Breakers



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia