R20-7-850-DIM

Project:	Туре:	Prepared By:	Date:
USTED.	<image/> <image/> <text><text></text></text>	lamps Constructed Rated for use Frosted lens Longer lifesp and mainten ENERGY STA	
Technical Specificat Performance	ions Dimmable:		Base Type:
Product Type:	Yes, down to 10	0%	E26
	L70 Lifespan:		Beam Angle:

Product Type:	res, down to T0%	E20
Reflector	L70 Lifespan:	Beam Angle:
Input Wattage:	25,000-Hour LED lifespan based on IES LM-70 results	110°
7W	Construction	Electrical
Lumens (Nominal):	Bulb Shape:	Power Factor:
525	R20	>0.9
Efficacy:	Enclosure Material:	Input Voltage:
75 lm/W	Plastic	120V
Color Accuracy:	Housing Finish:	Operating Temperature:
80	White	-20°C - 40°C
Color Temperature:	Lens Finish:	
5000K	Frosted	

Technical Specifications (continued) Other Compliance Rohs: Mercury and UV free. RoHS-compliant components. **UL Listed: Equivalency:** FCC: 50W Yes **Technology EQ:** Complies with Part 15 of the FCC Rules **Environment/Fixture Rating:** Model Number: Incandescent Damp / Enclosed R20-7-850-DIM Warranty (Years): **Energy Star ID:** RAB warrants that our LED products will be free from 2329466 defects in materials and workmanship for a period of

Dimension

three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty</u>.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	10	13.2	5.5	4.4
PALLET	2500	46.3	39.6	35.3



