ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685



R31 1X1/2 EX-PRF REDUCER

HUBBELL INCORPORATED DELAWARE

Catalog Number	R31
Manufacturer	HUBBELL INCORPORATED DELAWARE
Description	1" to 1/2" Reducing Bushing, Aluminum
Weight per unit	3.0 (lbs/each)
Product Category	Aluminum

Material, Color, and Finish

Color	Silver
Finish	Untreated

Dimensions and Weight

Height	0.81
Hub Size	1" to 1/2"
Length	1.32
Width	1.32

Descriptions

Description	1X1/2 EX-PRF REDUCER
Long Description	1" to 1/2" Reducing Bushing, Aluminum
Product Type	1" to 1/2" Reducing Bushing Al
Special Features	Killark's reducing bushings and adapters assist in reducing the trade size of tapped holes and its smooth internal bushing protects conductors. The wide variety of reducing ranges allow for almost any combination of size changes. It is available in copper-free aluminum and zinc plated steel.
Extra Long Description	KIL R-31 1" TO 1/2" REDUCING BUSHIN

Manufacturer Information

Brand	KILLARK
	Killark, a Hubbell affiliate
GTIN	00783936570020
Manufacturers Part Number	R-31
UPC	565656
Series	R Series

Taxonomies, Classifications, and Categories

Category Description	PVC SPACERS
Type	Reducing Bushing

Packaging

Carton	1
Package	50
Weight Per Each	3.0 (lbs/each)

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

Uses, Certifications, and Standards

Application	To reduce the trade size of a taped hole or hub.
Standard	UL, CSA

REDUCING BUSHINGS AND ADAPTERS



R- 31



R- 65



ADUP-12

Class I, Div. 1 & 2, Groups A,B,C,D
Class I, Zone 1, Groups IIC, IIB, IIA
Class II, Div. 1 & 2, Groups E,F,G

UL Standard: 1203
CSA Standard: C22.2 No. 30

UL LISTED File No. E 10514

CSA Certified File No. LR11716

FEATURES-SPECIFICATIONS

Application

- To reduce the trade size of a taped hole or hub.

Reducer Features

- Tapered threads (NPT)
- Smooth internal bushing protects conductors
- Threaded for Rigid Conduit or IMC

ADUP Features

- Tapered threads (NPT)
- Enlarged drilled and tapped hole openings by an NPT size

Material/Finish

Copper-free Aluminum
(less than 4/10 of 1%)
(R-10 through R-109)

Natural Finish

Steel/Zinc Plated
(RE20S through RE109S)

For ATEX and IEC Ex certified Reducing Bushings and Adapters, contact factory or check the website

REDUCING BUSHINGS

CATALOG NUMBER		HUB SIZE	DIMENSIONS
KILLARK ALUM.	STEEL		BODY LENGTH
R-10	—	1/2" — 3/8"	3/4"(19)
R-20	RE20S	3/4" — 3/8"	11/16"(18)
R-21	RE21S	3/4" — 1/2"	13/16"(21)
R-30	RE30S	1" — 3/8"	11/16"(18)
R-31	RE31S	1" — 1/2"	13/16"(21)
R-32	RE32S	1" — 3/4"	13/16"(21)
R-41	RE41S	1-1/4" — 1/2"	13/16"(21)
R-42	RE42S	1-1/4" — 3/4"	13/16"(21)
R-43	RE43S	1-1/4" — 1"	1"(25)
R-51	RE51S	1-1/2" — 1/2"	13/16"(21)
R-52	RE52S	1-1/2" — 3/4"	13/16"(21)
R-53	RE53S	1-1/2" — 1"	1"(25)
R-54	RE54S	1-1/2" — 1-1/4"	1-1/64"(28)
R-61	RE61S	2" — 1/2"	13/16"(21)
R-62	RE62S	2" — 3/4"	13/16"(21)
R-63	RE63S	2" — 1"	1"(25)
R-64	RE64S	2" — 1-1/4"	1/64"(28)
R-65	RE65S	2" — 1-1/2"	1/32"(31)
R-73	RE73S	2-1/2" — 1"	1"(25)
R-74	RE74S	2-1/2" — 1-1/4"	1" (25)
R-75	RE75S	2-1/2" — 1-1/2"	1"(25)
R-76	RE76S	2-1/2" — 2"	1"(25)
R-84	RE84S	3" — 1-1/4"	1" (25)
R-85	RE85S	3" — 1-1/2"	1-1/4"(32)
R-86	RE86S	3" — 2"	1-1/4"(32)
R-87	RE87S	3" — 2-1/2"	1-1/4"(32)
R-96	RE96S	3-1/2" — 2"	1-3/8"(35)
R-97	RE97S	3-1/2" — 2-1/2"	1-3/8"(35)
R-98	RE98S	3-1/2" — 3"	1-3/8"(35)
R-106	RE106S	4" — 2"	1-1/2"(38)
R-107	RE107S	4" — 2-1/2"	1-1/2"(38)
R-108	RE108S	4" — 3"	1-1/2"(38)
R-109	RE109S	4" — 3-1/2"	1-1/2"(38)

Material/Finish

Copper-free Aluminum
(less than 4/10 of 1%)

Natural Finish

ADUP ADAPTERS

CATALOG NUMBER	DESCRIPTION	
ADUP-01	Male 3/8"	Female 1/2"
ADUP-12	Male 1/2"	Female 3/4"
ADUP-23	Male 3/4"	Female 1"

MADE IN THE USA

HKFL-R-RE-ADUP 10-18 © Killark, 2018

KILLARK®

Hubbell Killark
3940 Dr. Martin Luther King Drive • St. Louis, MO 63113
Phone: (314) 531-0460 • Fax: (314) 531-7164
www.hubbell-killark.com

HUBBELL®
Harsh & Hazardous