



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



R43 1-1/4X1 Ex-PRF Reducer *Hubbell--Killark*

| | |
|------------------|---|
| Catalog Number | R43 |
| Manufacturer | Hubbell--Killark |
| Description | 1-1/4" to 1" Reducing Bushing, Aluminum |
| Weight per unit | 1.4 (lbs/each) |
| Product Category | Aluminum |

Features

| | |
|----------|--|
| Material | Aluminum, Copper Free (less than 4/10 of 1%) |
|----------|--|

Material, Color, and Finish

| | |
|--------|-----------|
| Color | Silver |
| Finish | Untreated |

Dimensions and Weight

| | |
|----------|--------------|
| Height | 2 |
| Hub Size | 1-1/4" to 1" |
| Length | 1 |
| Width | 2 |

Descriptions

| | |
|------------------------|--|
| Description | 1-1/4X1 EX-PRF REDUCER |
| extra long description | KLRK R-43 1-1/4" TO 1" REDUCING BUS |
| Long Description | 1-1/4" to 1" Reducing Bushing, Aluminum |
| Product Type | 1-1/4" to 1" Reducing Bushing |
| Special Features | Killark's reducing bushings and adapters assist in reducing the trade size of tapped holes and its smooth internal bushing protects conductors. The wide variety of reducing ranges allow for almost any combination of size changes. It is available in copper-free aluminum and zinc plated steel. |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | KILLARK |
| GTIN | 00783936570068 |
| Manufacturers Part Number | R-43 |
| series | R |
| UPC | 783936570068 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|------------------|
| Category Description | PVC SPACERS |
| Type | Reducing Bushing |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

| | |
|-----------------|--------|
| Carton | 1 |
| Package | 20 |
| Weight Per each | 1.3999 |

Uses, Certifications, and Standards

| | |
|-------------|--|
| Application | To reduce the trade size of a taped hole or hub. |
| standard | UL, CSA |