

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



REN20 100A 250V Superlag Renewable Fuse Bussmann Fuses

Catalog Number	REN20
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Ren Fuse, Time Lag, Non
	Current-Limiting, Industrial and Commercial Structures, 20 A,
	Class H, Non-Indicating, Ferrule End X Ferrule End, 10 Kaic,
	Standard, 10, 250 V
Weight per unit	·
Product Category	Tools & Testers
Features	
amperage rating	20
class	Class H
connection	Ferrule End X Ferrule End
dimensions	0.5600 IN X 0.5600 IN X 2.0000 IN
interrupt rating	10
media	Yes
Voltage Rating	250 V
Dimensions and Weight	
Size	0.56 In Diameter X 2.00 In Length
Descriptions	Q
Description	100A 250V SUPERLAG RENEWABLE FUSE
extra long description	BUSS REN-20 SUPER LAG RENEWABLE FUS
Features	Non-current limiting, renewable 250V (REN) and 600V (RES) Clas
. 60.00	H size fuses and fuse links (250V LKN and 600V LKS) for use in
	electrical systems where the available fault current is less than
	10,000 amps and frequent outages dictate the economy of these
	renewable type fuses.
Long Description	Eaton Bussmann series REN fuse, time lag, non current-limiting,
	Industrial and commercial structures, 20 A, Class H,
	Non-indicating, Ferrule end x ferrule end, 10 kAIC, Standard, 10,
	250 V
Product Type	Super Lag Renewable Fuse 20/250
Special Features	Super lag, time lag, non current-limiting
Manufacturer Information	
Brand	Eaton
GTIN	00051712100205
Manufacturers Part Number	REN-20
UPC	051712100205



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

1	Taxonomies,	Class	sifications,	and Ca	ategories

Category Description	Fuses & Fuse Accessories	
Туре	FUSE	
Packaging		
Carton	10	
Weight Per each	0.05	
Uses Cartifications and Stand	rdc	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	Not Applicable,RoHS Compliant