



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## RSP3 1" Cond 1-Hub Plate

*Crouse-Hinds*

Catalog Number	RSP3
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series RS/RSM Conduit Hub Plate, 8-1/2" X 4", Feraloy Iron Alloy, 1 Hub, 1" Trade Size
Weight per unit	2.4 (lbs/each)
Product Category	Cast Boxes

### Features

dimensions	3.5000 IN X 0.4700 IN X 8.0600 IN
Material	FERALOY IRON ALLOY

### Dimensions and Weight

Height	8.06
Length	3.5
Size	1 in
Width	0.47

### Descriptions

Description	1" COND 1-HUB PLATE
extra long description	CRS-H RSP3 1 1 HUB PLATE 8 1/2 X 4
Features	Crouse-Hinds series RS, RSM and RSS junction boxes are installed in conduit systems to act as pull boxes for conductors, provide openings and space for making splices and taps in conductors, provide for branch conduit runs, and provide access to conductors for maintenance and future system changes. RS, RSM and RSS junction boxes are designed with configurable conduit hub plates, permitting a wide range of hub arrangements and sizes.
Long Description	Eaton Crouse-Hinds series RS/RSM conduit hub plate, 8-1/2" x 4", Feraloy iron alloy, 1 hub, 1" trade size
Product Type	1 1 Hub Plate 8 1/2 X 4 Side RS/RSM BX
Special Features	Number of Hubs 1, For Use With 8-1/2 In X 4 In Sides of RS and RSM Boxes

### Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274597508
Manufacturers Part Number	RSP3
UPC	782274597508



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	HUB STYLE BOXES (GUAB, GUAT, ETC)
Type	Conduit Hub Plate

## Packaging

Carton	1
Package	2
Weight Per each	2.35

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
standard	UL, CSA C22.2