

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

				65
11	$\gamma_{1}$	$\sim$	$( \cap$	611
	- 20			

## RSP333 Hub W/3 1" Holes Crouse-Hinds

Catalog Number	RSP333		
Manufacturer	Crouse-Hinds		
Description	Eaton Crouse-Hinds Series RS/RSM Conduit Hub Plate, 8-1/2" X		
	4", Feraloy Iron Alloy, 3 Hubs, 1" Trade Size		
Weight per unit	2.7 (lbs/each)		
Product Category	Cast Boxes		
Features			
dimensions	8.0000 IN X 1.2500 IN X 3.5000 IN		
Material	FERALOY IRON ALLOY		
Dimensions and Weight			
Size	1 in		
Descriptions			
Description	HUB W/3 1" HOLES		
extra long description	CRS-H RSP333 1 3 HUB PLATE 8 1/2 X		
Features	Crouse-Hinds series RS, RSM and RSS junction boxes are installed		
	in conduit systems to act as pull boxes for conductors, provide		
	openings and space for making splices and taps in conductors,		
	provide for branch conduit runs, and provide access to		
	conductors for maintenance and future system changes. RS,		
	RSM and RSS junction boxes are designed with configurable		
	conduit hub plates, permitting a wide range of hub arrangements		
	and sizes.		
Long Description	Eaton Crouse-Hinds series RS/RSM conduit hub plate, 8-1/2" x 4",		
	Feraloy iron alloy, 3 hubs, 1" trade size		
Product Type	1 3 Hub Plate 8 1/2 X 4 Sides RS/RSM BX		
Special Features	For Use With 8-1/2 In X 4 In Sides Of Box		
Manufacturer Information			
Brand	EATON CROUSE-HINDS SERIES		
GTIN	00782274598901		
	RSP333		
UPC	782274598901		
Taxonomies, Classifications, and	Categories		
Category Description	HUB STYLE BOXES (GUAB, GUAT, ETC)		
Туре	Conduit Hub Plate		
Packaging			
Carton			
Weight Per each	2.68		



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Uses, Certifications, and Standards

Application standard

Ind Facilities & Factories - Facility: Power Distribution and Control UL 514A, CSA C22.2