

Motion Sensors Wt. Catalog # Description so Sensor only, 1500 watt INC capacity, 120V bronze .7 lbs: Motion Sensors for security and welcome lighting. SO-W S Series units have wide 270° field and kits have aluminum Sensor only, 1500 watt INC capacity, 120V white lampholders and cover. Center focal range is 50-75 feet. S2LH Sensor, twin 150 watt lampholders, coverplate, bronze 1.7 lbs S2LH-W M Series has 130° detection field, 40 foot center range and S2LH-W Sensor, twin 150 watt lampholders, coverplate, white 1.7 lbs non-metallic lampholders and cover. Sensor has 1/2" knuckle mount, adjustable time on and sensitivity controls. Bronze or МО Sensor only, 500 watt INC capacity, 120V bronze white finish. UL listed for wet locations. MO-W Sensor only, 500 watt INC capacity, 120V white .5 lbs M2LH Sensor, twin 150 watt lampholders, coverplate, bronze 1.2 lbs M2LH-W Sensor, twin 150 watt lampholders, coverplate, white 1.2 lbs R2LHQ Sensor, twin 75 watt quartz decorative lampholders 1.5 lbs Quartz motion sensors. Attractive security floodlight set. Powerful 75 watt G8 quartz floods controlled by 130° and coverplate, bronze, lamps included motion sensor so you save energy - lights only when you R2LHQ-W Sensor, twin 75 watt quartz decorative lampholders 1.5 lbs need it! and coverplate, white, lamps included **R2LHQ-W**

WALKWAY & PATH

Louverlight	S	Catalog	#	Wt.	Description
# .		587M-VG 583M-VG	Two Tier, 60 watt max. 120V, verdi Three Tier, 100 watt max. 120V, verdi	2.75 lbs 3.25 lbs	Louverlights illuminate and accent walkways, driveways and flower beds. Metal construction, verdi finish, frosted glass globes for source brightness reduction, 1/2" hub, UL wet location listed.
587M-VG	F				c (V) L) us
	583M-VG	GP12BL	Ground post with stabilizers, non-metallic, black	2.50 lbs	Ground post, PVC construction with 4 stabilizers and cap.
GP12BL					

LAMP HOLDERS

Lampholders	Catalog #	Wt.	Description
101-B 103-7 309 SERIES	101-B 103-71 103-74 309-M51-ML 309-M54-ML	Unshielded, 150 watt max., 120V bronze Shielded, 150 watt max., 120V bronze Shielded, 150 watt max., 120V white Deep shielded, 150 watt max., 120V bronze 3 lbs Deep shielded, 150 watt max., 120V white 3 lbs	Cast aluminum units with protective powder paint finish. A variety of unshielded, shielded, and deeply shielded designs for various application requirements. 1/2" cast aluminum swivel knuckle mounting. For use in wet locations. Universal aiming capability. Use PAR lamps outdoors (309 Series can use PAR or BR lamps outdoors). 101-B c L U U U S 103-7 309



Motion Sensors Wt. Catalog # Description so Sensor only, 1500 watt INC capacity, 120V bronze .7 lbs: Motion Sensors for security and welcome lighting. SO-W S Series units have wide 270° field and kits have aluminum Sensor only, 1500 watt INC capacity, 120V white lampholders and cover. Center focal range is 50-75 feet. S2LH Sensor, twin 150 watt lampholders, coverplate, bronze 1.7 lbs S2LH-W M Series has 130° detection field, 40 foot center range and S2LH-W Sensor, twin 150 watt lampholders, coverplate, white 1.7 lbs non-metallic lampholders and cover. Sensor has 1/2" knuckle mount, adjustable time on and sensitivity controls. Bronze or МО Sensor only, 500 watt INC capacity, 120V bronze white finish. UL listed for wet locations. MO-W Sensor only, 500 watt INC capacity, 120V white .5 lbs M2LH Sensor, twin 150 watt lampholders, coverplate, bronze 1.2 lbs M2LH-W Sensor, twin 150 watt lampholders, coverplate, white 1.2 lbs R2LHQ Sensor, twin 75 watt quartz decorative lampholders 1.5 lbs Quartz motion sensors. Attractive security floodlight set. Powerful 75 watt G8 quartz floods controlled by 130° and coverplate, bronze, lamps included motion sensor so you save energy - lights only when you R2LHQ-W Sensor, twin 75 watt quartz decorative lampholders 1.5 lbs need it! and coverplate, white, lamps included **R2LHQ-W**

WALKWAY & PATH

Louverlight	S	Catalog	#	Wt.	Description
# .		587M-VG 583M-VG	Two Tier, 60 watt max. 120V, verdi Three Tier, 100 watt max. 120V, verdi	2.75 lbs 3.25 lbs	Louverlights illuminate and accent walkways, driveways and flower beds. Metal construction, verdi finish, frosted glass globes for source brightness reduction, 1/2" hub, UL wet location listed.
587M-VG	F				c (V) L) us
	583M-VG	GP12BL	Ground post with stabilizers, non-metallic, black	2.50 lbs	Ground post, PVC construction with 4 stabilizers and cap.
GP12BL					

LAMP HOLDERS

Lampholders	Catalog #	Wt.	Description
101-B 103-7 309 SERIES	101-B 103-71 103-74 309-M51-ML 309-M54-ML	Unshielded, 150 watt max., 120V bronze Shielded, 150 watt max., 120V bronze Shielded, 150 watt max., 120V white Deep shielded, 150 watt max., 120V bronze 3 lbs Deep shielded, 150 watt max., 120V white 3 lbs	Cast aluminum units with protective powder paint finish. A variety of unshielded, shielded, and deeply shielded designs for various application requirements. 1/2" cast aluminum swivel knuckle mounting. For use in wet locations. Universal aiming capability. Use PAR lamps outdoors (309 Series can use PAR or BR lamps outdoors). 101-B c L U U U S 103-7 309