

# Calbrite™

## Stainless Steel Conduit Systems

### Stainless Steel Strut Clamps

#### Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Designed for use with 1-5/8" stainless channel
- No package qty. required
- Type 316 stainless steel nut & bolt included




#### Certifications and Compliances:

Calbrite stainless steel strut clamps are fabricated to UL and ASTM A167, F593 standards

#### Applications:

Used at any point along the slot side of the channel and are inserted into the two channel returns. Designed for use in standard 1-5/8" channels. Supplied with stainless nut and bolt.



#### Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Mills
- Along with other corrosive environments

Size	Part Number	Material Thickness	Design Load (lbs.)	Bolt Size	Weight per 100 (lbs.)
1/2"	S60500SC00	0.060"	400	1/4 -20 x 3/4"	11
3/4"	S60700SC00	0.060"	600	1/4 -20 x 3/4"	12
1"	S61000SC00	0.075"	600	1/4 -20 x 3/4"	16
1-1/4"	S61200SC00	0.075"	600	1/4 -20 x 3/4"	18
1-1/2"	S61500SC00	0.105"	800	5/16-18 x 1"	26
2"	S62000SC00	0.105"	800	5/16-18 x 1"	31
2-1/2"	S62500SC00	0.105"	800	5/16-18 x 1"	35
3"	S63000SC00	0.105"	800	5/16-18 x 1"	41
3-1/2"	S63500SC00	0.120"	1000	3/8-16 x 1-1/4"	50
4"	S64000SC00	1.120"	1000	3/8-16 x 1-1/4"	62

*All dimensions are for informational purposes only \*Tolerances +/- 5%*

# Calbrite™

## Stainless Steel Conduit Systems

### Stainless Steel Strut Clamps

#### Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Designed for use with 1-5/8" stainless channel
- No package qty. required
- Type 316 stainless steel nut & bolt included




#### Certifications and Compliances:

Calbrite stainless steel strut clamps are fabricated to UL and ASTM A167, F593 standards

#### Applications:

Used at any point along the slot side of the channel and are inserted into the two channel returns. Designed for use in standard 1-5/8" channels. Supplied with stainless nut and bolt.



#### Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Mills
- Along with other corrosive environments

Size	Part Number	Material Thickness	Design Load (lbs.)	Bolt Size	Weight per 100 (lbs.)
1/2"	S60500SC00	0.060"	400	1/4 -20 x 3/4"	11
3/4"	S60700SC00	0.060"	600	1/4 -20 x 3/4"	12
1"	S61000SC00	0.075"	600	1/4 -20 x 3/4"	16
1-1/4"	S61200SC00	0.075"	600	1/4 -20 x 3/4"	18
1-1/2"	S61500SC00	0.105"	800	5/16-18 x 1"	26
2"	S62000SC00	0.105"	800	5/16-18 x 1"	31
2-1/2"	S62500SC00	0.105"	800	5/16-18 x 1"	35
3"	S63000SC00	0.105"	800	5/16-18 x 1"	41
3-1/2"	S63500SC00	0.120"	1000	3/8-16 x 1-1/4"	50
4"	S64000SC00	1.120"	1000	3/8-16 x 1-1/4"	62

*All dimensions are for informational purposes only \*Tolerances +/- 5%*