



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

7604 Gateway Blvd
77521-0000, TX Baytown
Phone: 832-514-7819
Fax: 832-514-7820



SB384NM 1-1/4" Non-Metallic Split Bushing

Nsi Industries

| | |
|------------------|--|
| Catalog Number | SB384NM |
| Manufacturer | Nsi Industries |
| Description | Split Bushing, Insulated, Plastic, 1-1/4 Inch Trade Size. Patented |
| Weight per unit | 0.0220 (lbs/each) |
| Product Category | Plastic |

Features

| | |
|----------|---------------|
| Material | Nylon Plastic |
| media | Yes |

Material, Color, and Finish

| | |
|--------|-----------|
| Color | Gray |
| Finish | NO FINISH |

Dimensions and Weight

| | |
|------|-------|
| Size | 1-1/4 |
|------|-------|

Descriptions

| | |
|------------------------|--|
| Description | 1-1/4" NON-METALLIC SPLIT BUSHING |
| extra long description | BPT SB-384NM 1-1/4 IN Non-Metallic |
| Features | Split Bushings install after the wire pull. No more burning through bushings or fighting with pullers. Save time and effort too! |
| Long Description | Split Bushing, Insulated, Plastic, 1-1/4 Inch Trade Size. Patented |
| Product Type | 1-1/4 In Non-Metallic Split Bush, Box Of 20 |

Manufacturer Information

| | |
|---------------------------|---------------------|
| Brand | Bridgeport Fittings |
| GTIN | 00781747403841 |
| Manufacturers Part Number | SB-384NM |
| UPC | 781747403841 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---|
| Category Description | COUPLINGS, ADAPTERS, REDUCERS, BUSHINGS, & CAPS |
| Type | BUSHING |

Trade Size

| | |
|------------|------|
| Trade Size | 1.25 |
|------------|------|

Packaging

| | |
|-----------------|-------|
| Carton | 20 |
| Package | 200 |
| Weight Per each | 0.022 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

7604 Gateway Blvd
77521-0000, TX Baytown
Phone: 832-514-7819
Fax: 832-514-7820

Uses, Certifications, and Standards

Application

Used in situations where wires have already been pulled through Rigid/IMC conduit, and an insulated bushing is required. Rated 105 Degree C. cULus listed

standard

cULus

Temperature Rating

105 Degree C