

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



SC30 3/0 Cu Butt Splice Nsi Industries

Catalog Number	SC30
Manufacturer	Nsi Industries
Description	Standardbarrel TINNEDCOPPERSPLICE3/0 Awg Standard Barrel
	Tinned Coppersplices Is A Type Of Copper Compression
	Connector That Is Produced From High Conductivity Copper
	Tubing. They Are Tin-Plated to Provide Corrosion Resistance and
	Are Marked With Die Index and Color Coded For Easy Reference
	Listed For 35KV Maximum When Properly Installed.
Weight per unit	0.0800 (lbs/each)
Product Category	Large Terminals & Connectors
eatures	
Material	Copper
Number of Conductors	2
Poles	1
Voltage Rating	
Warranty	1 YEAR
Material, Color, and Finish	
Color	Orange
Finish	Tin Plated
Dimensions and Weight	
Size	L=1.75 - OD=.620 - ID=.490
Descriptions	
Description	3/0 CU BUTT SPLICE
extra long description	
Features	StandardBarrel TinnedCopperSplice3/0 AWG Standard Barrel
	Tinned CopperSplices is a type of copper compression connector
	that is produced from high conductivity copper tubing. They are
	tin-plated to provide corrosion resistance and are marked with
	die index and color coded for easy reference. Listed for 35KV
	maximum when properly installed.
Long Description	StandardBarrel TinnedCopperSplice3/0 AWG Standard Barrel
	Tinned CopperSplices is a type of copper compression connector
	that is produced from high conductivity copper tubing. They are
	tin-plated to provide corrosion resistance and are marked with
	die index and color coded for easy reference. Listed for 35KV
	maximum when properly installed.
Product Type	5
Special Features	3/0 AWG (STR) - CU Splice



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	NSi
GTIN	00662381037084
Manufacturers Part Number	SC-3/0
UPC	662381037084
Taxonomies, Classifications, and Ca	ategories
Category Description	Comp & Mech Lugs and Butt Splices
Туре	Short Barrel - CU Splice
Packaging	
Carton	1
Package	25
Weight Per each	0.08
Uses, Certifications, and Standards	
Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486
Temperature Rating	90 C