Industrial Optics and Accessory Matrix



CTEELED Aluminum High Pou

		STEELER Aluminum High-Bay							
High Pressure Sodium Multi-Tap Housing		HPSS-XXX-MT							
Metal Halide Multi-Tap Housing		MHSS-XXX-MT							
Metal Halide Multi-Tap Open Rated Socket Housing		MHSS-XXX-MT-OR*							
Metal Halide 5-Tap Housing Metal Halide 5-Tap Open Rated Socket Housing Metal Halide Multi-Tap Housing with Quartz Restrike Metal Halide Multi-Tap Open Rated Socket Housing with Quartz Restrike Pulse Start Metal Halide Multi-Tap Housing Pulse Start Metal Halide Multi-Tap Open Rated Socket Housing		MHSS-XXX-5T MHSS-XXX-5T-0R* MHSS-XXX-MT-Q MHSS-XXX-MT-0R-Q* MPSS-XXX-MT MPSS-XXX-MT							
					Wattage - Substitute X with available wattage.		70-450W	70-450W	400-1000W
					Optics		SA15	SA18	SA23
					Optics with Quartz Mounting		SA15E	SA18E	SA23E
					Acrylic Drop Lens		-	-	-
					Flat Glass Bottom	\bigcirc	SGB15*	SGB18*	SGB23*
Wire Guard		WG15	WG18	WG23					
Wire Guard (For drop lens)		-	-	-					
Gym Wire Guard with Safety Glass		WG15/GLC*	WG18/GLC*	WG23/GLC*					
Mounting Accessories									
CORD (C3) 3' 16/3 white cord (order hook separately)	\bigcirc	5	\checkmark	\checkmark					
HOOK (FH-1) Die-cast aluminum hook with 3/4" threads		V	\checkmark	\checkmark					
LOOP (FL-1) Malleable iron plated fixture loop with 3/4" threads		V	\checkmark	\checkmark					
SAFETY HOOK (SHK) Die-cast aluminum hook with safety screw and 3/4" threads	Ģ	1	\checkmark	1					
THRU-WAY MOUNTING BOX (TWMBS) Surface mounted thru-way mounting box		\checkmark	\checkmark	1					
CORD & PLUG (PC3-120V) 3' Cord with NEMA 120V L5-15P Plug		\checkmark	1	\checkmark					
CORD & PLUG (PC3-208V) 3' Cord with NEMA 208V L6-15P Plug		1	5	1					
CORD & PLUG (PC3-240V) 3' Cord with NEMA 240V L6-15P Plug		\checkmark	5	1					
CORD & PLUG (PC3-277V) 3' Cord with NEMA 277V L7-15P Plug		\checkmark	5	1					
CORD & PLUG (PC3-480V) 3' Cord with NEMA 480V L8-20P Plug		\checkmark	\checkmark	\checkmark					

*NEC 2005 Compliant



To build an industrial fixture select a ballast pod, inserting the desired wattage available in place of the X's, and the designated optic. For 400W Metal Halide 15" aluminum high-bay with a flat glass bottom enclosure the bill of material will read: MHSS-400-MT, SA15, and SGB15.

Industrial Optics and Accessory Matrix



CTEELED Aluminum High Pou

		STEELER Aluminum High-Bay							
High Pressure Sodium Multi-Tap Housing		HPSS-XXX-MT							
Metal Halide Multi-Tap Housing		MHSS-XXX-MT							
Metal Halide Multi-Tap Open Rated Socket Housing		MHSS-XXX-MT-OR*							
Metal Halide 5-Tap Housing Metal Halide 5-Tap Open Rated Socket Housing Metal Halide Multi-Tap Housing with Quartz Restrike Metal Halide Multi-Tap Open Rated Socket Housing with Quartz Restrike Pulse Start Metal Halide Multi-Tap Housing Pulse Start Metal Halide Multi-Tap Open Rated Socket Housing		MHSS-XXX-5T MHSS-XXX-5T-0R* MHSS-XXX-MT-Q MHSS-XXX-MT-0R-Q* MPSS-XXX-MT MPSS-XXX-MT							
					Wattage - Substitute X with available wattage.		70-450W	70-450W	400-1000W
					Optics		SA15	SA18	SA23
					Optics with Quartz Mounting		SA15E	SA18E	SA23E
					Acrylic Drop Lens		-	-	-
					Flat Glass Bottom	\bigcirc	SGB15*	SGB18*	SGB23*
Wire Guard		WG15	WG18	WG23					
Wire Guard (For drop lens)		-	-	-					
Gym Wire Guard with Safety Glass		WG15/GLC*	WG18/GLC*	WG23/GLC*					
Mounting Accessories									
CORD (C3) 3' 16/3 white cord (order hook separately)	\bigcirc	5	\checkmark	\checkmark					
HOOK (FH-1) Die-cast aluminum hook with 3/4" threads		V	\checkmark	\checkmark					
LOOP (FL-1) Malleable iron plated fixture loop with 3/4" threads		1	\checkmark	\checkmark					
SAFETY HOOK (SHK) Die-cast aluminum hook with safety screw and 3/4" threads	Ģ	1	\checkmark	1					
THRU-WAY MOUNTING BOX (TWMBS) Surface mounted thru-way mounting box		\checkmark	\checkmark	1					
CORD & PLUG (PC3-120V) 3' Cord with NEMA 120V L5-15P Plug		\checkmark	1	\checkmark					
CORD & PLUG (PC3-208V) 3' Cord with NEMA 208V L6-15P Plug		1	5	1					
CORD & PLUG (PC3-240V) 3' Cord with NEMA 240V L6-15P Plug		\checkmark	5	1					
CORD & PLUG (PC3-277V) 3' Cord with NEMA 277V L7-15P Plug		\checkmark	\checkmark	1					
CORD & PLUG (PC3-480V) 3' Cord with NEMA 480V L8-20P Plug		\checkmark	\checkmark	\checkmark					

*NEC 2005 Compliant



To build an industrial fixture select a ballast pod, inserting the desired wattage available in place of the X's, and the designated optic. For 400W Metal Halide 15" aluminum high-bay with a flat glass bottom enclosure the bill of material will read: MHSS-400-MT, SA15, and SGB15.