PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 23247

DESCRIPTION: 14/2 STRANDED TYPE SJEOOW FLEXIBLE POWER CABLE

This cable consists of two bare copper insulated conductors cabled with fillers and an overall jacket. UL Standard 62. CSA 22.2 No. 49. NEC Article 400. CONSTRUCTION:

APPROVALS:

APPLICATION: 300V Portable Oil and Water Resistant Submersible Outdoor Flexible Power Cable Construction Parameters:	
Electrical Properties:	
Temperature Rating Operating Voltage DC Resistance per Conductor @ 20°C	-60°C to 105°C 300 V RMS Max. 2.58 Ohms/1M' Nom.
Insulation Colors Jacket Color	Black White Yellow (Other colors available for minimum order) CCI Suprene 105 14 AWG (2.08mm²) 2/C SJEOOW E54864 (UL) 300V -60C TO 105C CSA LL39753 SJTOOW (TPE) -50C TO 105C FT2 WATER-RESISTANT
Legend (Black Surface Ink Print)	, ,
This product complies with European Directive 2002/95/NO special orders, the customer will accept all factory lengths and +/- 10	
The information presented here is, to the best of our knowledge, true ar control all product data presented is for informational purposes only and or confer any rights on any customer. The sale of products(s) is conditicable's standard terms and conditions contained therein, including with disclaims all liability in connection with the use of information contained	l does not create a binding obligation or liability on Coleman Cable oned upon acceptance of a purchase order subject to Coleman out limitation Coleman Cable's standard warranty. Coleman cable
This specification is proprietary intellectual property of Coleman Cable. party without written consent of Coleman Cable.	Any information contained herein shall not be disclosed to any
Customer Name	Date Signed
Customer Approval	

Specification Issue Date: March 22, 2007