

Vinyl Splice For 12 - 10 AWG

By Burndy Catalog # SP10

Copper Splice, 12-10 AWG, 1.23" Splice Length, Vinyl Insulated.



Application

For Accommodating A Broad Range Of 600 Volt Cables

General

Color Code Yellow

Connector Type Seamless Butt Splice

EU RoHS Indicator Yes

Feature - Barrel Style Shrouded

Insulation Y
Insulation Type Vinyl
Material Copper

Plated Y
Plating Type Tin

Sub Brand VINYLINK
Temperature Rating 105° C
Trade Name VINYLINK™

Type SP

UPC 781810710012 UPC 12 Digit 7818107100122

Dimensions

Cable Insulation Diameter 0.260 in

Maximum

Dimension - Diameter Max 0.26 in

Size inch

Dimension - L Length Overall 31 mm

mm

Dimension - Length Overall 1.23 in

inch

Dimension - Outside Diameter 0.26 in

inch

Dimension - Strip Length inch 21/64 in

Electrical Ratings

Voltage - Maximum 600 V

Conductor Related

Conductor - Copper Str Size 12 AWG;10 AWG Conductor - Copper Str Size 12 - 10 AWG

Range

Conductor Size 12 - 10 AWG

Certifications and Compliance

Certification - CSA Approved Yes
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No
Standards - Industry UL486

Standards Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Carton Quantity 480
Minimum Pack Quantity 40
Pallet Quantity 99999

Product Assets

3D Models - SP10_MODEL-IGES

3D Models - SP10_MODEL-PDF

3D Models - SP10_MODEL-STEP

Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice

Sales Drawings - 50094190