



# SP85/50/MED



|                      |                                   |
|----------------------|-----------------------------------|
| <b>Description</b>   | 85W 120V Spiral 5000K Medium Base |
| <b>Ordering Code</b> | 81181                             |
| <b>UNSPSC Code</b>   | 39101619                          |

## Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Voltage Rating</b>               | 120   |
| <b>Watts</b>                        | 85  |
| <b>Base Type</b>                    | Medium Screw (E26)  |
| <b>MOL in/mm</b>                    | 9.96/253  |
| <b>MOD in/mm</b>                    | 4.02/102  |
| <b>Approx Initial Lumens</b>        | 5350  |
| <b>CT deg K</b>                     | 5000  |
| <b>CRI</b>                          | >80   |
| <b>Rated Life</b>                   | 10,000  |
| <b>Special Desc</b>                 | Not for use with dimmers, electronic timers, photocells, motion/occupancy sensors, or in totally enclosed fixtures. Use in dry locations only. Use in open socket type fixtures only. |
| <b>Ambient Operating Temp Range</b> | 40° C (104° F) max. Open socket type fixture.   |

[watch](#) > [like](#) > [follow](#)



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 • (P) 1.800.852.2217 (F) 1.800.492.8975  
Canada: 81 King St, Barrie, ON L4N 6B5 • (P) 1.888.410.8151 (F) 1.888.705.1335



# SP85/50/MED



|                      |                                   |
|----------------------|-----------------------------------|
| <b>Description</b>   | 85W 120V Spiral 5000K Medium Base |
| <b>Ordering Code</b> | 81181                             |
| <b>UNSPSC Code</b>   | 39101619                          |

## Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Voltage Rating</b>               | 120   |
| <b>Watts</b>                        | 85  |
| <b>Base Type</b>                    | Medium Screw (E26)  |
| <b>MOL in/mm</b>                    | 9.96/253  |
| <b>MOD in/mm</b>                    | 4.02/102  |
| <b>Approx Initial Lumens</b>        | 5350  |
| <b>CT deg K</b>                     | 5000  |
| <b>CRI</b>                          | >80   |
| <b>Rated Life</b>                   | 10,000  |
| <b>Special Desc</b>                 | Not for use with dimmers, electronic timers, photocells, motion/occupancy sensors, or in totally enclosed fixtures. Use in dry locations only. Use in open socket type fixtures only. |
| <b>Ambient Operating Temp Range</b> | 40° C (104° F) max. Open socket type fixture.   |

[watch](#) > [like](#) > [follow](#)



selection. solutions. simplicity. [eiko.com](http://eiko.com)

23220 W. 84<sup>th</sup> St, Shawnee, KS 66227 • (P) 1.800.852.2217 (F) 1.800.492.8975  
Canada: 81 King St, Barrie, ON L4N 6B5 • (P) 1.888.410.8151 (F) 1.888.705.1335