

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Catalog Number	SPM27L
Manufacturer	Nsi Industries
Description	Service Post Connector - Two Wire Type 2-2 Awg Service Post Connectors Is Used For Connecting One or Two Conductors. Made From High Copper Content Hard-Drawn Rod. Lay-In Feature Makes Them Excellent For Continuous Loop Grounding and Bonding. Used to Ground to Bar or Plate. Suitable For Direc Burial In Earth or Concrete.
Weight per unit	3.1 (lbs/each)
Product Category	Large Terminals & Connectors
atures	
Material	Copper
Number of Conductors	
Poles	1
Voltage Rating	600 V
Warranty	1 YEAR
Wire Size	2 SOL - 2 STR
Wire Type	Class A & B
aterial, Color, and Finish	
Color	Copper
Finish	COPPER
mensions and Weight	
Size	Stud=1/2 x 13-1 1/4 - Hex Nut=7/8 x 14



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions	
Description	2, 2/0 SERVICE POST CONNECTOR 1/2 X 1-1/4
extra long description	NSI SPM-27L Service Post Two Wire 2
Features	Service Post Connector - Two Wire Type 2-2 AWG Service Post Connectors is used for connecting one or two conductors. Made from high copper content hard-drawn rod. Lay-in feature makes them excellent for continuous loop grounding and bonding. Used to ground to bar or plate. Suitable for direct burial in earth or concrete.
Long Description	Service Post Connector - Two Wire Type 2-2 AWG Service Post Connectors is used for connecting one or two conductors. Made from high copper content hard-drawn rod. Lay-in feature makes them excellent for continuous loop grounding and bonding. Used to ground to bar or plate. Suitable for direct burial in earth or concrete.
Product Type	Service Post Two Wire 2-2 Awg
Special Features	2 SOL-2 STR - 6 Pack
Manufacturer Information	
Brand	NSi
GTIN	00662381021168
Manufacturers Part Number	SPM-27L
UPC	662381021168
Taxonomies, Classifications, and Ca	ategories
Category Description	SPLIT BOLTS
Туре	Service Post Connectors
Packaging	
Carton	6
Weight Per each	3.12
Uses, Certifications, and Standards	;
Application	Wire Termination
environmental conditions	90 C
standard	UL486B
Temperature Rating	90 C