



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



SS701 Wallplate, 2-G, 2.48", SS *Hubbell Wiring Devices*

Catalog Number	SS701
Manufacturer	Hubbell Wiring Devices
Description	Wallplates and Boxes, Metallic Plates, 2- Gang, 1) 2.48" Opening, Standard Size, Stainless Steel.
Weight per unit	0.3500 (lbs/each)
Product Category	Wall Plates & Covers

Features

cutout	1) 2.48" Opening
gang	2-Gang
orientation	Vertical Mount
pallet quantity	8000

Dimensions and Weight

Size	2-Gang
Thickness	0.035

Descriptions

Construction	Stamped
Description	WALLPLATE, 2-G, 2.48", SS
extra long description	HPW SS701 WALLPLATE, 2-G, 2.48", SS
Features	Stainless steel wallplates provide solutions for a variety of industrial and commercial applications. 302/304 Type Stainless Steel Non-magnetic: 18.0% Chromium, 8% Nickel - Ideal for highly corrosive environments such as hospitals, food processing, static free requirements and more; ideal for environments subjected to heavy abuse. 430 Type Stainless Steel Magnetic: 17.0% Chromium, less than 0.5% Nickel - Aesthetically identical to the 302/304 type stainless steel wallplates and are best suited for environm
Long Description	Wallplates and Boxes, Metallic Plates, 2- Gang, 1) 2.48" Opening, Standard Size, Stainless Steel.
Product Type	Wallplate, 2-G, 2.48", SS
Special Features	Protective film helps to prevent scratches and damageProvides a plush appearance with the durability of metalBrass and Aluminum are lacquer coated to inhibit oxidation

Manufacturer Information

Brand	WIRING DEVICE-KELLEMS
GTIN	00883778201110
Manufacturers Part Number	SS701
UPC	883778201110



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Residential plates
Type	Plates

Packaging

Carton	1
Package	10
Weight Per each	0.35

Uses, Certifications, and Standards

Application	Protection against contact of live terminals and wiring. Provides finished look to installation.
Mounting	Screw Mounting
standard	UL Listed