

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

STAKS2X2AL03SWW7 26-45W 2X2 Led Center Basket Layin 35K/4K/5K Lithonia Lighting	
STAKS2X2AL03SWW7	
Lithonia Lighting	
Available In 2X2 and 2X4 Configurations, Stack Switch Provides Both Functionality and Efficiency. Selectable Lumens Allow For A Variety Of Mounting Heights and Switchable Color Temperature Allows You to Fine-Tune The Look Of Your Space.Stack Switch Is The Fully Switchable Version Of The Next-Generation Family Of Products. It Is The Perfect Choice For Schools, Commercial Office Spaces, and Many More Applications.	
9.3 (lbs/each)	
Lighting	
60,000	
23.8 x 23.9 x 2	
Yes	
Yes	
Yes	
LED - Dynamic	
3000 LM,4000 LM,5000 LM,Switchable	
Steel	
30	
Yes	
1	
Hardwired	
Square	
120-277	
41	
White	
82	
3500 ,4000 ,5000 ,Variable	
Matte	
WHITE	
Polycarbonate	
Traditional	



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Height	2
Length	
Width	23.9
Descriptions	
Construction	New Construction, Remodel
Description	
extra long description	
Features	Contractor Select
Long Description	Available in 2x2 and 2x4 configurations, STACK Switch provides both functionality and efficiency. Selectable lumens allow for a variety of mounting heights and switchable color temperature allows you to fine-tune the look of your space.STACK Switch is the fully switchable version of the next-generation family of products. It is the perfect choice for schools, commercial office spaces, and many more applications.
Product Type	Troffor
Nanufacturer Information	
Brand	Lithonia Lighting
GTIN	00194995082056
Manufacturers Part Number	STAKS 2X2 ALO3 SWW7
UPC	194995082056
axonomies, Classifications, and (Categories
Category Description	LED ARCHITECTURAL & SPECIFICATION LIGHTING
Туре	Troffer
rade Size	
aperture size	2x2
ackaging	
Carton	
Weight	7.05
Weight Per each	9.26
ses, Certifications, and Standard	ls
Application	Education, Government, Healthcare, Hospitality, Offices & Banks
environmental conditions	Indoor
Mounting	Recessed
standard	CSADLC Standard