Eaton T20P11S10CU

Catalog Number: T20P11S10CU

General-Purpose Transformer, Ventilated, Dry Type Distribution, DS-3, Single-phase, PV: 240 X 480V, Taps: 1 at +5% FCAN, 2 at -5% FCBN X 2 at +2.5% FCAN, 4 at -2.5% FCBN, SV: 120/240V, 150°C, 10 kVA, Cu windings, Frame: 815, uses WS15





Catalog Number

Eaton General purpose ventilated

T20P11S10CU

transformer

UPC

786680065156

Product Length/Depth

Product Height

15.82 in

30.25 in

Product Width

Product Weight

16.87 in

182 lb

Certifications

Warranty

Eaton Selling Policy 25-000, one (1) year Contact Manufacturer

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.



Photo is representative



Physical Attributes

Coil material

Copper

Design

DS-3

Frame

815

Tap size

1 at +5% FCAN, 2 at -5% FCBN x 2 at +2.5% FCAN, 4 at -2.5%

FCBN

Type

Dry Type Distribution Transformer

Performance Ratings

Frequency rating

60 Hz

Kva Rating

10 kVA

Primary voltage

240 V, 480 V

Secondary Voltage

120/240 V

Temperature rise

150 °C rise

Miscellaneous

Weathershield

WS15

Resources

Catalogs

Eaton's Volume 2—Commercial Distribution

Specifications and datasheets

Eaton Specification Sheet - T20P11S10CU



Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia



Eaton T20P11S10CU

Catalog Number: T20P11S10CU

General-Purpose Transformer, Ventilated, Dry Type Distribution, DS-3, Single-phase, PV: 240 X 480V, Taps: 1 at +5% FCAN, 2 at -5% FCBN X 2 at +2.5% FCAN, 4 at -2.5% FCBN, SV: 120/240V, 150°C, 10 kVA, Cu windings, Frame: 815, uses WS15





Catalog Number

Eaton General purpose ventilated

T20P11S10CU

transformer

UPC

786680065156

Product Length/Depth

Product Height

15.82 in

30.25 in

Product Width

Product Weight

16.87 in

182 lb

Certifications

Warranty

Eaton Selling Policy 25-000, one (1) year Contact Manufacturer

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.



Photo is representative



Physical Attributes

Coil material

Copper

Design

DS-3

Frame

815

Tap size

1 at +5% FCAN, 2 at -5% FCBN x 2 at +2.5% FCAN, 4 at -2.5%

FCBN

Type

Dry Type Distribution Transformer

Performance Ratings

Frequency rating

60 Hz

Kva Rating

10 kVA

Primary voltage

240 V, 480 V

Secondary Voltage

120/240 V

Temperature rise

150 °C rise

Miscellaneous

Weathershield

WS15

Resources

Catalogs

Eaton's Volume 2—Commercial Distribution

Specifications and datasheets

Eaton Specification Sheet - T20P11S10CU



Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia

