

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



T20P11S5016 50KVA Ventd XFMR DOE2016 Eff 1PH 240X480-120/240 1 *Eaton Corp*

Catalog Number	T20P11S5016
Manufacturer	Eaton Corp
Description	Eaton General Purpose Ventilated Transformer, Nema 2, FR843A 60 HZ, 50 Kva, Single-Phase, 240X480V, 120/240 V, Nema ST-20, 1 At +5%, 2 At -5% X 2 At +2.5%, 4 At -2.5%, 50 Kva, 240 X 480 Vac-120/240 V, 3XA, Doe 2016
Weight per unit	408.0 (lbs/each)
Product Category	20160728100210
Features	
dimensions	24.3800 IN X 23.5100 IN X 38.7000 IN
Efficiency	10 CFR Part 431-2016 (DOE 2016)
Insulation Class	220 °C
kva rating	50
Number of Phases	Single-phase
Primary Voltage	240 V, 480 V
Secondary Voltage	120/240 V
Tap Size	1 at +5%, 2 at -5% x 2 at +2.5%, 4 at -2.5%
Descriptions	
Description	50KVA VENTD XFMR DOE2016 EFF 1PH 240X480-120/240 1
extra long description	ETN T20P11S5016 50KVA 1PH 240X480-1
Features	Eaton types DS-3 (single-phase) and DT-3 (three-phase) general purpose ventilated dry-type transformers are two-winding, self-cooled, and available in a wide variety of primary and secondary voltage combinations. General purpose transformers are designed for continuous operation at rated kVA. They are designed, manufactured and tested in accordance with all of the latest applicable ANSI, NEMA and IEEE standards.
Long Description	Eaton General purpose ventilated transformer, NEMA 2, FR843A 60 Hz, 50 kVA, Single-phase, 240X480V, 120/240 V, NEMA ST-20, 1 at +5%, 2 at -5% x 2 at +2.5%, 4 at -2.5%, 50 kVA, 240 X 480 Vac-120/240 V, 3XA, DOE 2016
Product Type	50KVA 1PH 240X480-120/240 150C
Special Features	Fungus-resistent varnished core and coil
Manufacturer Information	
Brand	Eaton
GTIN	00786680147647
Manufacturers Part Number	T20P11S5016
UPC	786680147647



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cat	
Category Description	1 PHASE TRANSFORMERS
Туре	Ventilated transformer
Packaging	
Carton	1
Weight Per each	408
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Power Distribution and Controls
Frequency Rating	60
Mounting	Floor or wall, upright only
standard	OSHPD Certified, UL Listed, DOE 2016 Efficient

Temperature Rating 150 °C rise