



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1701 Commerce Rd  
71601-7613, AR Pine Bluff  
Phone: 870-671-4805  
Fax: 870-671-4806



## **T279740S 1KVA 1PH Transformer** *Acme Electric*

Catalog Number	T279740S
Manufacturer	Acme Electric
Description	Low Voltage Distribution Transformer - Single Phase, 120/208/240/277 - 120/240V, 1kva
Weight per unit	23.0 (lbs/each)
Product Category	Single Phase Non Ventilated to

### **Features**

pallet quantity	20
Primary Voltage	120/208/240/277
product category	Dry Type Distribution Transformer
Secondary Voltage	120/240

### **Dimensions and Weight**

Height	10.5
Length	5.13
Width	5.5

### **Descriptions**

Construction	ENCAPSULATED
Description	1KVA 1PH TRANSFORMER
extra long description	ACME T279740S TFM R 1PH 1.0KVA 120/2
Long Description	Low Voltage Distribution Transformer - Single Phase, 120/208/240/277 - 120/240V, 1kVA
Product Type	Dry Type Distribution Transformer
Special Features	Encapsulated core and coil; Shielded for cleaner power; Encapsulated and completely enclosed design electrical grade silica and resin compounds completely enclose the core and coil to seal out all moisture and air, UL type 3R enclosure for indoor or outdoor service, encapsulation eliminates corrosion and insulation deterioration; Quiet operation with sound levels well below NEMA standards; 10-year limited warranty

### **Manufacturer Information**

Brand	ACME ELECTRIC
GTIN	00047503102008
Manufacturers Part Number	T279740S
UPC	047503102008

### **Taxonomies, Classifications, and Categories**

Category Description	1 PHASE TRANSFORMERS
Type	Distribution Transformer



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1701 Commerce Rd  
71601-7613, AR Pine Bluff  
Phone: 870-671-4805  
Fax: 870-671-4806

## Packaging

Carton	1
Weight Per each	23

## Uses, Certifications, and Standards

Enclosure	NEMA 3R Steel
Mounting	WALL
standard	UL 506, UL File Number E79947V1, UL Control Number 50B8, UL Insulation Number X3221, CSA Certified, OSHA Compliant, ANSI, IEEE
Temperature Rating	115 DEG C Rise