

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



T50FC0 Panduit T50F-C0 Polyethylene Spiral Wrap *Panduit Corporation*

Panduit Corporation The T50F-C0 Polyethylene Spiral Wrap Provides Continuous
The T50F-C0 Polyethylene Spiral Wrap Provides Continuous
Abrasion Protection For Wires, Cables, and Tubing. The Spiral
Wrap Harnesses Multiple Cables Into A Single Manageable
Bundle While Allowing For Breakouts. Lightweight, Flexible,
Durable Protection Allows For Use With Irregular Shapes. Rated
For Use Up to 122°F (50°C). 0.50" (12.7 MM) Diameter X 100'
(30.5 M) Long. Bundle Diameter Range 0.375" to 4" (9.5 MM to 101.6 MM). Color Black.
5.4 (lbs/each)
Cable Ties & Wraps
•
Polyethylene
4
Yes
0.375
0.5
0.06
Black
100
PANDUIT T50F-C0 POLYETHYLENE SPIRAL WRAP
PAN T50F-C0 T50F-C0 Spiral Wrap, BI
The T50F-C0 Polyethylene Spiral Wrap provides continuous
abrasion protection for wires, cables, and tubing. The spiral wrap
harnesses multiple cables into a single manageable bundle while
allowing for breakouts. Lightweight, flexible, durable protection
allows for use with irregular shapes. Rated for use up to 122°F
(50°C). 0.50" (12.7 mm) diameter x 100' (30.5 m) long. Bundle Diameter Range 0.375" to 4" (9.5 mm to 101.6 mm). Color Black.
T50F-C0 Spiral Wrap, Black, Uv Pe, 0.375" Min Dia., 100' Rol



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

IV	laı	nut	act	urei	r Ini	orr	mat	ion

Brand	PANDUIT	
GTIN	00074983706099	
Manufacturers Part Number	T50F-C0	
UPC	074983706099	

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Туре	Spiral Wrap

Packaging

onaging	
Carton	1
Weight Per each	5.35

Uses, Certifications, and Standards

Application	Harness Multiple Cables Into a Single Manageable Bundle; Allows
	Breakouts of Single/Multiple Cables; Provides Abrasion
	Protection for Wire, Cables, Hoses, and Tubing
standard	UL Recognized - E141152; UL94HB
Temperature Rating	122