PRO

Operation Manual

PRO

Operation Manual

T721

Pro1 Technologies
1111 S. Glenstone Ave., Suite 3 -100
Springfield, MO 65804
Toll Free: 888-776-1427
Web: www.pro1iaq.com
Hours of Operation: M-F 9AM - 6PM Eastern

Table of Contents	Page
Table of Contents	1
Thermostat Operation	2-3
Thermostat Quick Reference	4-6
Thermostat Warranty Information	7


Caution

Equipment damage hazard. Do not operate the cooling system if the outdoor temperature is below 50 ˚F (10 ˚C) to prevent possible compressor damage.

Una version en español de este manual se puede descargar en la pagina web de la compañia.

® U.S. Registered Trademark. Patents pending
Copyright © 2017 All Rights Reserved.

Rev. 1712



1. LCD Display
2. Glow in the dark light button
3. Fan Switch
4. System Switch
5. Temperature Setpoint Buttons
6. Easy change battery door

Thermostat Operation

1 LCD Display

See page 4 for details about this display read out.

2 Glow in the dark light button

The glow in the dark light button will self illuminate for several hours after exposure to ambient light. This button turns on the display light when pressed.

3 Fan Switch

Select **ON** or **AUTO**. **ON** will run the fan continuously. **AUTO** will cycle the fan on only when the heating or cooling system is on.

4 System Switch


Selects the operation mode on your HVAC system. Selecting **HEAT** turns on the heat mode. Selecting **COOL** turns on the cool mode. Selecting **OFF** turns both heating and cooling off. Selecting **EmH** (for heat pumps with auxiliary heat) will lockout the compressor and control emergency/ auxiliary heat.

5 Temperature Setpoint Buttons

Press the + or - buttons to select the desired room temperature.


6 Easy Change Battery Door


See page 5 for details.



Thermostat Quick Reference

Battery Door Installation





Caution:

When the battery icon LOW appears replace your AA batteries immediately. Failure to do so may result in your heating & cooling system becoming inoperable. Freezing or over heating can occur.

Important:

The low battery indicator is displayed when the AA battery power is low. If the user fails to replace the battery within 21 days, the screen will only show the low battery indicator but maintain all functionality. If the user fails to replace the batteries after an additional 21 days (days 22-42 since first "low battery" display) the set points will change to 55˚F(Heating) and 85˚F(Cooling). If the user adjusts these setpoints away from these it will hold for 4 hours then return to either 55˚F or 85˚F. After day 63 the batteries must be replaced immediately to avoid freezing or overheating because the thermostat will shut the unit off until the battery is changed.

Warranty Registration

Your new thermostat has a 5 year limited warranty. You must register your thermostat within 60 days of installation. Without this registration the warranty period will begin on date of manufacture. For warranty issues please contact the HVAC professional that installed this product. You can register your new thermostat in 2 ways:

Online

Go to the company website, select warranty registration and fill out a short registration form.

Mail

Complete the form below and mail it to the address shown.

Warranty Registration

Name: _____

Address: _____

_____

City: _____

State: _____

Zip: _____

Thermostat Model: _____

Date Installed: _____

Complete form and mail to:

Thermostat Warranty Registration
1111 S. Glenstone
Suite 3-100
Springfield, MO 65804

Cut Out For
Warranty Registration

www.pro1iaq.com

PRO

Operation Manual

PRO

Operation Manual

T721

Pro1 Technologies
1111 S. Glenstone Ave., Suite 3 -100
Springfield, MO 65804
Toll Free: 888-776-1427
Web: www.pro1iaq.com
Hours of Operation: M-F 9AM - 6PM Eastern

Table of Contents	Page
Table of Contents	1
Thermostat Operation	2-3
Thermostat Quick Reference	4-6
Thermostat Warranty Information	7


Caution

Equipment damage hazard. Do not operate the cooling system if the outdoor temperature is below 50 ˚F (10 ˚C) to prevent possible compressor damage.

Una version en español de este manual se puede descargar en la pagina web de la compañia.

® U.S. Registered Trademark. Patents pending
Copyright © 2017 All Rights Reserved.

Rev. 1712



1. LCD Display
2. Glow in the dark light button
3. Fan Switch
4. System Switch
5. Temperature Setpoint Buttons
6. Easy change battery door

Thermostat Operation

1 LCD Display

See page 4 for details about this display read out.

2 Glow in the dark light button

The glow in the dark light button will self illuminate for several hours after exposure to ambient light. This button turns on the display light when pressed.

3 Fan Switch

Select **ON** or **AUTO**. **ON** will run the fan continuously. **AUTO** will cycle the fan on only when the heating or cooling system is on.

4 System Switch


Selects the operation mode on your HVAC system. Selecting **HEAT** turns on the heat mode. Selecting **COOL** turns on the cool mode. Selecting **OFF** turns both heating and cooling off. Selecting **EmH** (for heat pumps with auxiliary heat) will lockout the compressor and control emergency/ auxiliary heat.

5 Temperature Setpoint Buttons

Press the + or - buttons to select the desired room temperature.


6 Easy Change Battery Door


See page 5 for details.



Thermostat Quick Reference

Battery Door Installation





Caution:

When the battery icon LOW appears replace your AA batteries immediately. Failure to do so may result in your heating & cooling system becoming inoperable. Freezing or over heating can occur.

Important:

The low battery indicator is displayed when the AA battery power is low. If the user fails to replace the battery within 21 days, the screen will only show the low battery indicator but maintain all functionality. If the user fails to replace the batteries after an additional 21 days (days 22-42 since first "low battery" display) the set points will change to 55˚F(Heating) and 85˚F(Cooling). If the user adjusts these setpoints away from these it will hold for 4 hours then return to either 55˚F or 85˚F. After day 63 the batteries must be replaced immediately to avoid freezing or overheating because the thermostat will shut the unit off until the battery is changed.

Warranty Registration

Your new thermostat has a 5 year limited warranty. You must register your thermostat within 60 days of installation. Without this registration the warranty period will begin on date of manufacture. For warranty issues please contact the HVAC professional that installed this product. You can register your new thermostat in 2 ways:

Online

Go to the company website, select warranty registration and fill out a short registration form.

Mail

Complete the form below and mail it to the address shown.

Warranty Registration

Name: _____

Address: _____

_____

City: _____

State: _____

Zip: _____

Thermostat Model: _____

Date Installed: _____

Complete form and mail to:

Thermostat Warranty Registration
1111 S. Glenstone
Suite 3-100
Springfield, MO 65804

Cut Out For
Warranty Registration

www.pro1iaq.com