

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Category Description

Type

TB49 1-1/4" Alu TB MK9 Conduit Body *Crouse-Hinds*

Catalog Number	TB49			
Manufacturer	Crouse-Hinds			
Description	Eaton Crouse-Hinds Series Condulet Mark 9 Conduit Outlet Body Copper-Free Aluminum, TB Shape, 1-1/4"			
Weight per unit	1.4 (lbs/each)			
Product Category	Alum			
atures				
dimensions	8.5000 IN X 2.1900 IN X 3.3400 IN			
aterial, Color, and Finish				
Finish	Untreated			
mensions and Weight				
Height	3-15/32			
Hub Size	1-1/4 in			
Length	7-1/2			
Width	2-3/16			
scriptions				
Description	1-1/4" ALU TB MK9 CONDUIT BODY			
extra long description	CRS-H TB49 1 1/4 NPT CST AL TB MARK			
Features	Mark 9 copper-free aluminum conduit bodies, covers and gasket from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide for access to conductors for maintenance and future system changes. Mark 9 bodies are offered in seven different shapes, and they provide more room for heavier conductors.			
Long Description	Eaton Crouse-Hinds series Condulet Mark 9 conduit outlet body, Copper-free aluminum, TB shape, 1-1/4"			
Product Type	1 1/4 NPT CST AI TB Mark 9 CNDT Body			
anufacturer Information	FATON CROUGE HINDS SERVES			
Brand	EATON CROUSE-HINDS SERIES			
GTIN	00782274631349			
Manufacturers Part Number UPC	TB49 782274631349			

Form 9 condulets, covers & gaskets

Conduit outlet body



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

•			

Packaging	
Carton	1
Package	2
Weight Per each	1.43
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Condulet
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D