



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## TMRP Series Timing Relay

TMRP5102

UPC:786685215372

### Dimensions:

- **Height:** 1.88 IN
- **Length:** 3.46 IN
- **Width:** 1.88 IN

**Weight:** .25 LB

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Contact Configuration:** DPDT
- **Contact Material:** 90% silver, 10% nickel
- **Contact Rating:** 12A
- **Number Of Pins:** 8
- **Functions:** ON delay, power triggered, flasher-pause first, single shot leading edge voltage controlled
- **Input Voltage:** 12-240 Vac/dc
- **Operating Mode:** Power triggered
- **Options:** Plastic dust cover
- **Series:** TMRP series
- **Terminals:** Octal
- **Time Delay:** 0.1 seconds-9990 hours

### Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [Eaton Specification Sheet - TMRP5102](#)

### Certifications:

- UL Listed

### Product compliance:



- RoHS Compliant
- CE Marked

---

© 2016 Eaton. All rights reserved.



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## TMRP Series Timing Relay

TMRP5102

UPC:786685215372

### Dimensions:

- **Height:** 1.88 IN
- **Length:** 3.46 IN
- **Width:** 1.88 IN

**Weight:** .25 LB

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Contact Configuration:** DPDT
- **Contact Material:** 90% silver, 10% nickel
- **Contact Rating:** 12A
- **Number Of Pins:** 8
- **Functions:** ON delay, power triggered, flasher-pause first, single shot leading edge voltage controlled
- **Input Voltage:** 12-240 Vac/dc
- **Operating Mode:** Power triggered
- **Options:** Plastic dust cover
- **Series:** TMRP series
- **Terminals:** Octal
- **Time Delay:** 0.1 seconds-9990 hours

### Supporting documents:

- [Eaton's Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [Eaton Specification Sheet - TMRP5102](#)

### Certifications:

- UL Listed

### Product compliance:



- RoHS Compliant
- CE Marked

---

© 2016 Eaton. All rights reserved.