

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Size

#### TR2R 250V 2A 2X9/10 RK5 TD Fuse

Mersen Fuses

Catalog Number	TR2R
Manufacturer	Mersen Fuses
Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 2A Ferrule Tri-Onic®
Weight per unit	0.0500 (lbs/each)
Product Category	Current Limiting
Features	
AC Voltage Rating	250
amperage rating	2
class	Class RK5
connection	Ferrule
interrupt rating	200
Voltage Rating	250
Material, Color, and Finish	
Body Material	PolyTube
Dimensions and Weight	

2 x 0.56



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	2	~ r	1	•.	$\sim$	~~
	_					
_	es				v	
_			_		_	
			•			

Marcon TD2D Fuco TD D. Class DVE
Mersen TR2R Fuse TR-R - Class RK5 -
Tri-Onic TR-R current-limiting time-delay fuses are engineered for overcurrent protection of motors, transformers, service entrance equipment, feeders and branch-circuits. The time-delay characteristics of the TR-R safely handle harmless starting currents and inrush currents associated with today's motors and transformers.
Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 2A Ferrule Tri-Onic®
Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 2A Ferrule
250V 2A 2x9/10 RK5 TD FUS
Time-delay Current-limiting AC & DC rated Optional solid state SmartSpot blown fuse indicator Time-delay for motor start-ups and transformer inrush currents without nuisance opening Current-limiting for low peak let-thru current Rejection-style design prevents replacement errors (when used with recommended fuse blocks) Easy-to-read label for quick brand recognition and replacement Metal-embossed date and catalog number for traceability and lasting identification Fiberglass body provides dimensional stabili

## **Manufacturer Information**

Brand	Mersen
GTIN	00782001747640
Manufacturers Part Number	TR2R
sub brand	Tri-Onic ®
UPC	782001747640

### Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Туре	CLASS RK5

## **Packaging**

Carton	1
Package	10
Weight Per each	0.05

### Uses, Certifications, and Standards

Application	Motor circuits Mains Feeders Branch circuits Transformers
	Service entrance equipment General-purpose equipment
Mounting	Clip
standard	UL listed to standard 248-12 File E2137 CSA certified to standard
	C22.2 no. 248.12 DC listed to UL standard 248 TRS only