

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



TR70R 250V RK5 TD Fuse Mersen Fuses

Catalog Number	TR70R
Manufacturer	Mersen Fuses
Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 70A Blade Tri-Onic®
Weight per unit	0.3500 (lbs/each)
Product Category	Current Limiting
Features	
AC Voltage Rating	250
amperage rating	70
class	RK-5
connection	Blade
interrupt rating	200
Voltage Rating	250
Material, Color, and Finish	
Body Material	PolyTube
Dimensions and Weight	
Size	5.88 x 0.06



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

standard

Descriptions	
Description	250V RK5 TD FUSE
extra long description	Mersen TR70R Fuse TR-R - Class RK5
Features	Tri-Onic TR-R current-limiting time-delay fuses are engineered for overcurrent protection of motors, transformers, service entrance equipment, feeders and branch-circuits. The time-delay characteristics of the TR-R safely handle harmless starting currents and inrush currents associated with today's motors and transformers.
Long Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 70A Blade Tri-Onic®
Product Type Short Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 70A Blade 250V 70A 5 7/8x1 1/16 RK5
Special Features	Time-delay Current-limiting AC & DC rated Optional solid state SmartSpot blown fuse indicator Time-delay for motor start-ups and transformer inrush currents without nuisance opening Current-limiting for low peak let-thru current Rejection-style design prevents replacement errors (when used with recommended fuse blocks) Easy-to-read label for quick brand recognition and replacement Metal-embossed date and catalog number for traceability and lasting identification Fiberglass body provides dimensional stabili
Manufacturer Information	
Brand	Mersen
GTIN	00782001747978
Manufacturers Part Number	TR70R
sub brand	Tri-Onic ®
UPC	782001747978
Taxonomies, Classifications, and Cat	egories
Туре	CLASS RK5
Packaging Carton	1
Weight Per each	0.35
Uses, Certifications, and Standards	
Application	Motor circuits Mains Feeders Branch circuits Transformers Service entrance equipment General-purpose equipment
Mounting	Clip

UL listed to standard 248-12 File E2137 CSA certified to standard

C22.2 no. 248.12 DC listed to UL standard 248 TRS only