# Specifications







## Eaton TRL04

Eaton 4-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton TR timing relay |
| **CATALOG NUMBER** | TRL04 |
| **UPC** | 786685313573 |
| **PRODUCT LENGTH/DEPTH** | 1.3 in |
| **PRODUCT HEIGHT** | 3.43 in |
| **PRODUCT WIDTH** | 1.8 in |
| **PRODUCT WEIGHT** | 0.09 lb |
| **WARRANTY** | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| **COMPLIANCES** | CE Marked<br>TUV |
| **CERTIFICATIONS** | CSA Certified<br>cULus Listed |

Powering Business Worldwide

## Product specifications

| | |
|---|---|
| **FREQUENCY RATING** | 50-60 Hz |
| **ENCLOSURE** | IP40 |
| **ENCLOSURE MATERIAL** | Self-extinguishing plastic |
| **CONTACT CONFIGURATION** | SPDT |
| **TIME DELAY** | 0.05 seconds-100 hours |
| **SERIES** | TR |
| **FUNCTIONS** | ON/OFF delay<br>Power triggered<br>Single shot leading edge<br>voltage controlled<br>Flasher-pause first |
| **INPUT VOLTAGE** | 24-240 Vac/dc |
| **MOUNTING METHOD** | Compact DIN rail |

## Resources

| | |
|---|---|
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - TRL04 |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc**
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

# Specifications







## Eaton TRL04

Eaton 4-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton TR timing relay |
| **CATALOG NUMBER** | TRL04 |
| **UPC** | 786685313573 |
| **PRODUCT LENGTH/DEPTH** | 1.3 in |
| **PRODUCT HEIGHT** | 3.43 in |
| **PRODUCT WIDTH** | 1.8 in |
| **PRODUCT WEIGHT** | 0.09 lb |
| **WARRANTY** | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| **COMPLIANCES** | CE Marked<br>TUV |
| **CERTIFICATIONS** | CSA Certified<br>cULus Listed |

Powering Business Worldwide

## Product specifications

| | |
|---|---|
| **FREQUENCY RATING** | 50-60 Hz |
| **ENCLOSURE** | IP40 |
| **ENCLOSURE MATERIAL** | Self-extinguishing plastic |
| **CONTACT CONFIGURATION** | SPDT |
| **TIME DELAY** | 0.05 seconds-100 hours |
| **SERIES** | TR |
| **FUNCTIONS** | ON/OFF delay<br>Power triggered<br>Single shot leading edge<br>voltage controlled<br>Flasher-pause first |
| **INPUT VOLTAGE** | 24-240 Vac/dc |
| **MOUNTING METHOD** | Compact DIN rail |

## Resources

| | |
|---|---|
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - TRL04 |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc**
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.