ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2805 Poplar
75402-0000, TX Greenville
Phone: 903-454-3354
Fax: 903-454-8926

UAG34500 3/4" Ua Sealtite Conduit, Bonded Ul 500'

Southwire Company

Catalog Number	UAG34500
Manufacturer	Southwire Company
Description	TITAN2 Type Ul LFMC Is Manufactured With A Spiral Wound Strip Of Heavy Gauge Corrosion-Resistant Hot-Dipped Galvanized Steel. For 3/8" Through 1-1/4" Trade Sizes The Core Is Constructed With A Square Locked Steel Strip With An Integral Copperbonding Strip Enclosed Within The Steel Convolutions. For 1-1/2" Through 4" Trade Sizes The Core Is Constructed With A Fully Interlocked Steel Strip. A Rugged Flame Retardant Flexible PVC Jacket Is Extruded Over The Steel Core. The Grey Jacket Resists Oils Mild
Weight per unit	0.3800 (lbs/each)
Product Category	Conduit & Raceways

Features

outside diameter	1040

Dimensions and Weight

Length	500

Descriptions

Description	3/4" UA SEALTITE CONDUIT, BONDED UL 500'
extra long description	SWC 55082705 LTM-UL 3/4" GYJT 500R
Long Description	Titan2 Type UL LFMC is manufactured with a spiral wound strip of heavy gauge corrosion-resistant hot-dipped galvanized steel. For 3/8" through 1-1/4" trade sizes the core is constructed with a square locked steel strip with an integral copperbonding strip enclosed within the steel convolutions. For 1-1/2" through 4" trade sizes the core is constructed with a fully interlocked steel strip. A rugged flame retardant flexible PVC jacket is extruded over the steel core. The grey jacket resists oils mild
Product Type	LTM-Ul 3/4" Gyjt 500R
Short Description	LTM-UL 3/4" GyJt 500R

Manufacturer Information

Brand	Flexible Conduit
GTIN	00032886052637
Manufacturers Part Number	55082705
UPC	032886052637

Taxonomies, Classifications, and Categories

Category Description	Liquid Tight

2805 Poplar
75402-0000, TX Greenville
Phone: 903-454-3354
Fax: 903-454-8926

Trade Size

Trade Size	3/4

Packaging

Carton	500
Weight Per each	0.38