



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



UNF17 1/2"NPT Unf RGD Short FML Expn Union *Crouse-Hinds*

Catalog Number	UNF17
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Unf Expansion Union, Rigid/Imc, Female, Steel, 1/2", Short
Weight per unit	0.5700 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

connection	Female Threaded, Female Threaded
dimensions	2.8800 IN X 1.1900 IN X 1.1900 IN

Descriptions

Description	1/2"NPT UNF RGD SHORT FML EXPN UNION
extra long description	CRH UNF17 1/2 NPT FEMALE SHORT EXPA
Features	Crouse-Hinds series explosionproof unions are installed in rigid/IMC conduit systems to connect conduit to conduit, a conduit fitting, junction box or device enclosure. Expansion unions are also available, which allow for expansion and contraction of conduit and compensate for conduit cut too short. Available in a variety of materials, including stainless steel, to suit customer preferences. Explosionproof elbows allow for a 90° change in direction to the conduit run, or when terminating at a box or fit
Long Description	Eaton Crouse-Hinds series UNF expansion union, Rigid/IMC, Female, Steel, 1/2", Short
Product Type	1/2 NPT Female Short Expansion Union
Special Features	1-3/16 In Diameter X 3-3/8 In Length

Manufacturer Information

Brand	Eaton Crouse-Hinds
GTIN	00782274129112
Manufacturers Part Number	UNF17
UPC	782274129112

Taxonomies, Classifications, and Categories

Category Description	STEEL EMT FITTINGS
Type	Expansion union

Packaging

Carton	1
Weight Per each	0.57



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 Group E F G, Class II Div 2 Group F G, Class III
standard	UL 886, CSA C22.2